**100scans / sec USB αυτόματα laser σάρωση barcode scanner**
**(Μοντέλο: OCBs-LA06)**

## Προδιαγραφές του προϊόντος:

| | |
|---|---|
| **Χαρακτηριστικά** | |
| Πηγή: | Ορατό laser (650-670nm) |
| Ταχύτητα σάρωσης: | 100 σαρώσεις ανά δευτερόλεπτο |
| Απόσταση ανάγνωσης | 2.5 ~ 600 χιλιοστά (100% UPC / EAN) |
| Τύπος σάρωσης: | Αμφίδρομη |
| Ανάλυση: | 0,10 mm (4εκ) σε PCS 0,9 |
| Εκτύπωση Αντίθεση Χαμηλή: | 20%, η ελάχιστη διαφορά ανάκλασης (@ 650nm σε) |
| Δυνατότητες αποκωδικοποίησης: | UPC / EAN, UPC / EAN με supplementals, UCC / EAN128, κωδικός 39, κωδικός 39 πλήρη ASCII, κωδικός 39 trioptic, κωδικό 128, κωδικός 128 πλήρη ASCII, codabar, διαπλέκονται 2 από 5, 2 διακριτά από 5, κώδικας 93, MSI , κωδικός 11, ATA, παραλλαγές RSS, κινεζική 2 από 5 ... |
| **Φυσικά Χαρακτηριστικά** | |
| Διασυνδέσεις που υποστηρίζονται: | PS2, RS232, USB |
| Τάση: | DC + 5V +/- 5% |
| Τρέχουσα δουλειά: | 100 mA |
| Δεν φορτίο ρεύματος: | & Amp? Lt? 40 □□ |
| Τροφοδοσία: | Υποδοχής ρεύματος ή εξωτερική (RS232) εξουσία |
| Γωνία σάρωσης | Υψόμετρο γωνία 45 ° 60 ° |
| Διαστάσεις: | L165.42mm σημείο σημείο ¯xW69.72mm ¯xH89.67mm |
| Βάρος: | 140 g (με εξαίρεση βραχίονα στήριξης) |
| Στήριγμα | Συνοδεύεται με |
| Χρώμα: | Ivory ή Μαύρο |
| **Περιβάλλον Χρήστη** | |
| Θερμοκρασία εργασίας: | 0-50 degre eC |
| Θερμοκρασία αποθήκευσης: | -40 ~ 70degreeς |
| Υγρασία: | 5 ~ 95% σχετική υγρασία, χωρίς συμπύκνωση |
| Ηλεκτροστατική εκκένωση: | Επιβεβαιώστε με ± 15kV απαλλαγή αέρα και + 8KV της απαλλαγής επαφής |
| Πτώση προδιαγραφές αντίστασης: | Σκυρόδεμα μπορεί να αντέξει πολλαπλές δοκιμή πτώσης 1,5 m |
| **Ασφάλεια:** | |
| EMI / RFI: | FCC A και CE Class |
| Ασφάλεια Laser: | CDRH προϊόντα λέιζερ 2 |

## Λεπτομέρειες προϊόντος:

## Product Picture

## Features

Simple but not easy
Auto-Induction built in, green design
High scan rate and long reading

distance
Excellent decode capability
KBW, RS232 and USB supported

## All-round show

## Parameter

| Performance Characteristics | |
|---|---|
| Light Source: | Visible laser (650-670nm) |
| Scan Rate: | 100 scans per second |
| Reading Distance | 2.5 ~600mm (100% UPC/EAN) |
| Scanner Type: | Bi-directional |
| Resolution: | 0.10mm (4mil) at PCS 0.9 |
| Print Contrast Minimum: | 20%, minimum reflective difference (@650nm) |
| Decode Capability: | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5,discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5... |
| **Physical Characteristics** | |

| | |
|---|---|
| Interfaces Supported: | PS2, RS232, USB |
| Voltage: | DC+5V+/-5% |
| Current: | 100 mA |
| Idle Current: | <40 mA |
| Power Source: | Host power or external (RS232) power supply |
| Scanning Angle | Inclination 45° Elevation 60° |
| Dimensions: | L165.42mm X W69.72mm X H89.67mm |
| Weight: | 140g (without stand) |
| Stand | With |
| Color: | Ivory and black |
| **User Environment** | |
| Operating Temperature: | 0℃~50℃ |
| Storage Temperature: | -40℃~ 70℃ |
| Humidity: | 5~95% relative humidity, non-condensing |
| Electrostatic Discharge: | Confirm to +/-15KV air discharge and +/-8KV of contact discharge |
| Drop Specifications: | Withstands multiple 1.5m drops to concrete |
| **Safe:** | |
| EMI/RFI: | FCC Class A and CE |
| Laser Safety: | CDRH class 2 laser product |

## Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

www.ocominc.com

# Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.