

80mm High Speed Bluetooth POS Thermal Printer

(Model No.: OCPP-88A-BUL)

Features:

Unique appearance with reliable mould;
High Printing Speed up to 300mm/second;
auto Cutter ;
Cord and cordless communication for options
Interface: Bluetooth+USB+LAN
Sound and light alarm supported suitable for kitchen application;
Support multiple 1D and QR code types printing;
Support multi international languages;
SDK for Android available;
Reliable printer head with 100km life;
Compatible with EPSON ESC/POS commands.

Parameters:

| | |
|----------------------|---|
| Printing Method | Thermal line printing |
| Printing Character | 576dots/line (default), 512dots/line; Characters : Simplified Chinese 24x24 point, support 18030 font library, support Taiwan and HK traditional (complex font), ANK characters; |
| Font | A: 12*24dots,1.5(W)*3.0(H)mm; B: 9*17dots,1.1(W)*2.1(H)mm Simplified/Traditional : 24*24dots, 3.0(W)*3.0(H)mm |
| Barcode Type | JUPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128, QR code |
| Printing Speed | 250mm/sec for a single interface ,300mm/sec for Double interface and three interfaces |
| Interface | USB, USB+Serial, USB+ LAN, USB+ Serial+ LAN, Wifi+USB, Bluetooth+USB+LAN |
| Printing Command | Compatible with EPSON ESC/POS commands |
| Drivers | Win9X/ Window XP /Win2000/Win2003/Win Vista/ Win 7/ Win 8/win8.1/Linux, compatible with ESPON, SDK for Android available. |
| Printing Width | 79.5±0.5mm(print width 72mm) |
| Paper Diameter | 83mm |
| Paper Thickness | 0.06-0.08mm |
| Cutter | Auto cutter (optional) |
| Printing Reliability | 100km |
| Power | DC24V/2.5A |
| Temperature | 0-45 degree C |
| Contrast Humidity | 10-80% |
| External Dimension | 190*145*145(mm) |
| Weight | 1.60kg |

| | P/N | Description |
|----------------------|---------------|--|
| Ordering information | OCPP-88A-U | USB port, with auto cutter |
| | OCPP-88A-UR | USB+Serial port, with auto cutter |
| | OCPP-88A-UL | USB+Lan port, with auto cutter |
| | OCPP-88A-URL | USB+Serial+Lan port, with auto cutter |
| | OCPP-88A-W | Wifi+USB port, with auto cutter |
| | OCPP-88A-BUL | Bluetooth+USB+LAN, with auto-cutter |
| | OCPP-88A-U0 | USB port, without auto cutter |
| | OCPP-88A-UR0 | USB+Serial port, without auto cutter |
| | OCPP-88A-UL0 | USB+Lan port, without auto cutter |
| | OCPP-88A-URL0 | USB+Serial+Lan port, without auto cutter |
| | OCPP-88A-W0 | Wifi+USB port, without auto cutter |
| | OCPP-88A-BUL0 | Bluetooth+USB+LAN, without auto-cutter |

