

China Pos Thermal Receipt Printer

(Model: OCPP-585)

Specification:

printer, pos receipt printer, android receipt printer

Printing Method	Direct thermal
Print Density	384dots/line (203DPI)
Character Size	384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Barcode Type	JAN13 □ EAN13 □ JAN8 □ EAN8 □ CODE39 QR □ optional □
Printing Command	Compatible with PSON ESC/POS
Language	Buyer language support
Printing Speed	90mm/sec
Paper Width	57.5±0.5mm
Paper Thickness	0.06-0.08mm
MCBF(life)	50km
Dimension	190*132*119mm
Gross Weight	1.2KG
Auto Cutter	manual cutter
Sensor	Paper Near End Sensor, Paper End Sensor, Cover open sensor
Roll Paper	Φ75mm
Interface	RS-232C, Parallel, USB, LAN
Driver	Win 9X, Win 2000, Win 2003, Win XP, Win Vista, Win 7 compatible with ESPON
Adapter Voltage Input	AC 110V/220V, 50-60Hz
Adapter Voltage Output	DC12V/3A
Printer Input Voltage	DC12V/3A
Cash Drawer Control	DC12V/1A
Working Temperature	0-45°C, Humidity: 10-80%
Saving Temperature	-10-60°C, Humidity: 10-90%
Certificate	CE/FCC/CCC/RoHS

Product Details:

printer, pos receipt printer, android receipt printer



Relevant documents:

- *Specification
- *Program Manual
- *Instruction Manual
- *Driver for WinXP Win2000 WinVista Win7 Win8-32bit
- *Driver for Win7and Win8-64bit
- *Driver for Linux

*Printer Parameters Setting Tools

*USB Printdemo(Application Software demo)

*SDK for Android

*CD Files