

Τελευταίο φορητό σαρωτή για 1D / 2D Barcode

Τεχνολογία απεικόνισης υψηλής απόδοσης.

Ομοιόμορφη σάρωση, εύκολη σάρωση.

Μπορεί να διαβάσει τον γραμμωτό κώδικα στην οθόνη και το χρώμα του γραμμωτού κώδικα.

4mil εξαιρετική ακρίβεια σάρωσης;

Η ρύθμιση πολλαπλών ειδικών λειτουργιών υποστηρίζεται.

Πολλαπλές διεπαφές προαιρετικές.

Σταθείτε για επιλογή.

Χαρακτηριστικά απόδοσης

Λειτουργία		
Πηγή φωτός	Λευκή λυχνία LED	
Μπιπ	Υποστηριζόμενα	
Στάση	Προαιρετικός	
Δείκτης	Πράσινο LED, μπιπ	
Επιδόσεις σάρωσης		
Αισθητήρα	CMOS	
Ανάλυση	640 * 480.256 επίπεδα γκρι	
Μέγιστη ταχύτητα αποκωδικοποίησης	13 ml UPC 40 cm / s	
Γωνία ανάγνωσης	οριζόντια 50 μοίρες. κατακόρυφα 20 Deg	
Ακρίβεια	≥4mil	
Δυνατότητα αποκωδικοποίησης	1D	UPC-E, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved από 5 (διακριτά 2 από 5), μήτρα 2 από 5, Codabar (NW7), κώδικας 128, UCC / EAN 128 (GS1-128), ISBT 128, Code93, Code 11 (USD-8)
	2D	PDF417, MicroPDF417, QR κώδικα, DataMatrix, κώδικας Han Xin, κώδικας Aztec, GS1 Com pos ite
Βάθος πεδίου	Κωδικός 39 (5mil): 50mm ~ 120mm Κωδικός 39 (10mil): 25mm ~ 250mm UPC / EAN (13mil): 20mm ~ 320mm Δεδομένα Matrix (7.5mil): 63mm ~ 150mm PDF417 (6,6mil): 62mm ~ 145mm	
Ευαισθησία	Κλίση ± 45 ° @ 0 ° Roll και 0 ° κλίση Περιστροφή ± 30 ° @ 0 ° Pitch και 0 ° κλίση Απόκλιση ± 45 ° @ 0 ° Roll και κλίση 0 °	
Ηλεκτρικός		
Διεπαφή	USB, USB COM (εικονική σειριακή θύρα)	
Τάση εισόδου	3.3v ~ 5v DC	
Τυπική ισχύς	2.0w (400mA)	
Μέγιστη ισχύς	2.5w (450mA)	
Προσαρμογέα DC	Μέγ. 5.5V 1A	
LED CLASS	Κλάση I	
Δοκιμή EMC	FCC μέρος 15, IEC60825-1, EN55022 Κλάση B	
Περιβάλλον χρήστη		
Λειτουργία θερμοκρασίας	-20 ° C έως +60 ° C (-4 ° F έως 144 ° F)	
Θερμοκρασία αποθήκευσης	-30 ° C έως + 70 ° C (-22 ° F έως 158 ° F)	

Υγρασία	5% - 95% (χωρίς συμπύκνωση)
Αντοχή σε σταγόνες:	1,5m (1,0ft) σταγόνες στο σκυρόδεμα
IP τάξη	IP54
Ελαφριά ένταση	Εργασία: φώτα ηλίου, λαμπτήρες φθορισμού
Φυσικός	
Διαστάσεις	156 * 68 * 83mm
Βάρος	195 g (χωρίς βάση)
Διαστάσεις συσκευασίας	48 * 36 * 47CM (20 τεμάχια με βάση 13,5 KG)
	48 * 39 * 52CM (30 τεμάχια χωρίς βάση 15KG)



Handheld Image Scanner for 1D/2D Barcode

OCBS-2008



Product Picture




Features

Reliable with good price

- High performance imaging technology;
Omni-directional scanning, easy to scan;



- 4mil excellent scanning accuracy ;
Can read the barcode on the screen
and color barcode;



Multi special function setting supported;
SDK/API Available;



Multi interfaces optional;
Stand for option.



Application place



Bookstore



Supermakte



Pharmacy



Warehouse



Clothing store



Restaurant

Parameter

Function		
Light source	White LED	
Beep	Supported	
Stand	Optional	
Indicator	Green LED, beep	
Scan performance		
Sensor	CMOS	
Resolution	640*480,256 gray levels	
Maximum decoding speed	13mil UPC 40cm/s	
Reading angle	horizontally 50 deg; vertically 20 Deg	
Precision	≥4mil	
Decode capability	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128 (GS1-128), ISBT 128, Code93, Code 11 (USD-8), MSI/Plessey
	2D	PDF417, MicroPDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, GS1 Composite
Depth of field	Code 39(5mil): 50mm~120mm Code 39(10mil): 25mm~250mm UPC/EAN (13mil): 20mm~320mm Data Matrix(7.5mil): 63mm~150mm PDF417(6.6mil): 62mm~145mm	
Sensitivity	Inclination ±45° @0°Roll and 0°Skew Rotation ±30° @0°Pitch and 0°Skew Deflection ±45° @0°Roll and 0°Skew	
Electrical		
Interface	USB,USB COM(virtual serial port)	
Input Voltage	3.3v~5v DC	
Standard Power	2.0w (400mA)	
Max Power	2.5w (450mA)	
DC adapter	Max 5.5V 1A	
LED CLASS	Class I	
EMC Test	FCC part15,IEC60825-1,EN55022 Class B	
User Environment		
Operate Temperature	-20 deg C ~ +60 deg C (-4 Deg F to 144 deg F)	
Storage Temperature	-30 deg C ~ +70 Deg C (-22 Deg F to 158 deg F)	
Humidity	5% - 95%(non- condensation)	
Drop resistance:	1.5m (5.0ft) drops to concrete	
IP class	IP54	
Light intensity	Working: sun lights, fluorescent lights	
Physical		
Dimensions	156*68*83mm	
Weight	195 g (without stand)	
Package dimension	48*36*47CM (20pcs with stand 13.5KG)	
	48*39*52CM (30pcs without stand 15KG)	

Production Capacity:

✓ Indicates information has been verified onsite by a certification specialist

Production Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

Verified by TUV on 2013.7.15

Quality Assurance:



OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHs and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments:

✓ Indicates information has been verified onsite by a certification specialist

Test Equipment and Facilities

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

Verified by TUV on 2013.7.15

Certification:




Warranty and After Sales:



- ▶ All products' warranty are not less than 12 month, some models even up to 24 months warranty.
- ▶ Spare parts will be provided for mass orders for customers' local maintenance.
- ▶ Any product found to be defective within 30 days of shipment shall be deemed Dead on Arrival (DOA). DOA products will be advance replaced and shipped via express.
- ▶ Have distributors or authorized agents in the main market who can provide local repair and replacement services.
- ▶ Professional CRM management insures fast respond for customer's enquiries and orders tracking.
- ▶ Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility.
- ▶ 7*24 hours online, responds with 12 hours in working days, and within 24 hours for rest days.

Packing and Shipment:



Payment:



secure payment



Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.



Company Profile

TRADE ASSURANCE

- 100% money refund for Late shipment & Quality problem
- Guarantee on-time delivery
- Third-party pre-shipment quality inspection (Optional)
- No transaction commission charged
- The HIGHEST assurance amount guaranteed by alibaba in the Auto-ID and POS industry .



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers , Thermal Printer, Barcode printer, Dot Matrix Printer, Barcode Scanner, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.



Why you choose us?



Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: Unit701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: ocom@ocominc.com, info@possolution.com.cn ;

Tel: +86.755.86053207 ext 800;

Fax: +86.755.86053207 ext 868;

QQ: 2485890637, 190852203;

Wechat: szocominc, hj34924238;

Whatsapp: 008613352932860;



Σχετικά έγγραφα:

[USB Virtual Driver COM](#)

[Εγχειρίδιο χρήστη](#)

