

Θερμικής Μεταφοράς και Άμεση Θερμική Barcode εκτυπωτή ετικετών

(Μοντέλο: OCBP-002)

Προδιαγραφή:

Μοντέλο εκτυπωτή	OCBP-002
Ψήφισμα	203 DPI (8 dot / mm)
Μέθοδος εκτύπωσης	Απευθείας Θερμική / Θερμική μεταφορά
ΕΠΕΞΕΡΓΑΣΤΗΣ	32 BIT
Αισθητήρας	Είδος: Κενό ετικέτα και μαύρο ανίχνευσης σήματος Ανίχνευση: μήκος της ετικέτας αυτόματη ανίχνευση ή ρύθμιση εντολή πρόγραμμα
Ταχύτητα εκτύπωσης	50,8 χιλιοστά -101,6 χιλιοστά / δευτερόλεπτο
Εκτύπωση Μήκος	1.727 χιλιοστά
Πλάτος εκτύπωσης	25 χιλιοστά ~ 104 χιλιοστά
Μέσα ενημέρωσης	Χαρτί Roll Εξωτερική διάμετρος: Μέγιστη Διάμετρος 105 mm Χαρτί Roll Άξονας: 26 χιλιοστά Χαρτί Πλάτος: 25 χιλιοστά ~ 110 χιλιοστά Χαρτί Πάχος: 0,06 χιλιοστά ~ 0,3 χιλιοστά Μέσα ενημέρωσης Τύπος: κενό ετικέτα, πίσω σήμα, συνεχής
Κορδέλλα	Τύποι: Παθητική Roll Εξωτερική διάμετρος: 64 χιλιοστά (Max) 300M Μήκος Πλάτος: 30 χιλιοστά ~ 110 mm Πυρήνας Εσωτερική Διάμετρος: 25,4 χιλιοστά (1inch) Υλικό: Γενικά Wax Τύπος, κερί / ρητίνη μεικτού τύπου, Ρητίνη Τύπος
Μνήμη	2MB Flash Rom, 2MB DRAM
Εικόνα	Μονόχρωμος PCX, BMP (υποστήριξη μετά τον έλεγχο του λογισμικού: ICOWMFJPGEMF εικόνες, μπορεί να ελέγχουν την ενίσχυση της εικόνας, μειωμένο, περιστροφή, καθρέφτης της εικόνας και αποκορύφωμα
Bar Code	Code39, Code93, Code128 (υποσύνολο A, B, Γ), UPC A / E (add on 2 & amp? 5), Interleaved 2 5, EAN 8/13 (add on 2 & amp? 5), bar code, Κίνα T.K., Βιομηχανική 2 5, Matrix 2 από 5, PDF417 και στοιχείων Κωδικός μήτρα, (QR Code Διαθέσιμο), Δεδομένα Μήτρα
Διασύνδεση	Παράλληλο Λιμάνι + USB
Ρύθμιση Μεταφοράς	Baud Ισοτιμία 9600, XON / XOFF, RTS / CTS
Πίνακας Ελέγχου	LED * 2: Έτοιμος, Κατάσταση Λειτουργία Κλειδί * 1: Feed
Ισχύς	AC 18V, 4000mA
Περιβάλλον	Λειτουργικά Θερμοκρασία: 40 βαθμούς F έως 104 βαθμούς F (5 ° C για έως 40 βαθμούς C) Αποθήκευση Θερμοκρασία: -40 βαθμούς F έως 122 βαθμούς F (-20 ° C για έως 50 βαθμούς C) Λειτουργικά Υγρασία: 30% ~ 85%, χωρίς συμπύκνωση, χωρίς αέρα Αποθήκευση Υγρασία: 10% ~ 90%, χωρίς συμπύκνωση, χωρίς αέρα
Φυσική διάσταση	Μέγεθος: L286mm * H176mm * W233mm Βάρος: 2.43KG (Καθαρό)

Λεπτομέρειες προϊόντος:



Thermal Transfer and Direct Thermal Barcode Label Printer

OCBP-002



Product Picture





Features

Simple but not easy

Two printing methods available:
Thermal Transfer with ribbon and Direct Thermal;





Compatible with plenty of label software;
BMP, PCX images download store;

Support Parallel and USB together;



Suit for thermal paper rolls or
self-adhesive labels;

All-round show



Application Area



Warehouse



Tax Institution



Clothes Store



Airline service

Supermarket



Logistic freight

Drug Store



Bakery Shop



Parameter

Printer Model	OCBP-002
Resolution	203 DPI (8 dot/mm)
Printing Method	Direct Thermal / Thermal Transfer

CPU	32 Bit
Sensor	Type: Label gap and black mark sensing Detection: label length auto sensing or program command setting
Printing Speed	50.8 mm -101.6 mm / Sec
Printing Length	1727 mm
Printing Width	25 mm ~ 104 mm
Media	Paper Roll External Diameter: Maximum Diameter 105 mm Paper Roll Axis: 26 mm Paper Width: 25 mm ~ 110 mm Paper Thickness: 0.06 mm ~ 0.3 mm Media Type: Label gap, Back mark, Continuous
Ribbon	Types: Outward Roll External Diameter: 64mm (Max) Length 300M Width: 30 mm ~ 110 mm Core Inner Diameter: 25.4mm (1inch) Material: General Wax Type, Wax/Resin Mixed Type, Resin Type
Memory	2MB Flash Rom, 2MB DRAM
Image	Monochrome PCX, BMP (support after the software control: ICOWMFJPGEMF Picture, can control the picture amplification, reduced, rotation, mirror image and highlight
Bar Code	Code39, Code93, Code128 (subset A, B, C), UPC A/E (add on 2 & 5), Interleaved 2 of 5, EAN 8/13 (add on 2 & 5), Code bar, China Postal Code, Industrial 2 of 5, Matrix 2 of 5, PDF417 and Data matrix Code, (QR Code Available), Data Matrix
Interface	Parallel Port+ USB
Transmission Setting	Baud Rate 9600, XON/XOFF, RTS/CTS
Control panel	LED*2: Ready, Status Function Key*1: Feed
Power	AC 18V, 4000mA
Environment	Operating Temperature: 40°F to 104°F (5°C to 40°C) Storage Temperature: -40°F to 122°F (-20°C to 50°C) Operating Humidity: 30% ~ 85%, non-condensing, Free air Storage Humidity: 10% ~ 90%, non-condensing, Free air
Physical Dimension	Size: L286mm * H176mm *W233mm Weight: 2.43KG (net)

Production Line





Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

Certifications



Packing and Shipment



Payment





Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?



Company Profile

**This Assessed Supplier Has Been
Independently Verified**

Build Your Growth On Trust



TÜV Rheinland®





FOVHemana
Precisely Right.



OCOM Technologies Limited, founded in 2007, is one of the leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and are hot selling in Europe, Australia, Asia, and other areas.



OCOM has a professional team including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years. All of the sales have more than 5 years' experience, which helps us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like to establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

 Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,
Shenzhen 518054, China;

Websites: <http://www.possolution.com.cn> ; <http://www.ocominc.com> ;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



Σχετικά έγγραφα:

Θέλετε να μάθετε περισσότερα inf προϊόνormation; Παρακαλώ Κανε κλικ εδώ. 

[Προσδιορισμός](#)

[Driver για WIN7 Win 8](#)

[Λογισμικό για Win XP / Win 2000](#)