

Μίνι φορητός σαρωτής χειρός με αυτόματη λειτουργία Sense Handheld με Stand (Μοντέλο: OCBS-LA11)

Κύριο χαρακτηριστικό:

1D χειρός σαρωτής γραμμωτού κώδικα λέιζερ με λειτουργία αυτόματης αίσθησης.

Ευέλικτη λειτουργία με μεταλλική βάση περιστροφής 360 μοιρών.

Υψηλό ποσοστό σάρωσης (100 σάρωση / δευτ.) Και μεγάλη απόσταση ανάγνωσης.

Εξαιρετική ικανότητα αποκωδικοποίησης.

KBW, RS232 και USB υποστηρίζονται?

Γκρι και Μαύρο διαθέσιμο χρώμα.

ΠΡΟΔΙΑΓΡΑΦΕΣ:

Χαρακτηριστικά απόδοσης	
Πηγή φωτός:	Ορατό λέιζερ (650-670nm)
Ρυθμός σάρωσης:	100 σαρώσεις ανά δευτερόλεπτο
Απόσταση ανάγνωσης	2,5 ~ 600 mm (100% UPC / EAN)
Τύπος σαρωτή:	Αμφίδρομος
Ανάλυση:	0,10 mm (4 ml) στο PCS 0,9
Εκτύπωση Αντίθεση Ελάχιστο:	30%, ελάχιστη αντανακλαστική διαφορά (@ 650nm)
Ποσοστό σφάλματος:	1/3000000
Δυνατότητα αποκωδικοποίησης:	UPC / EAN, UPC / EAN με συμπληρωματικά στοιχεία, UCC / EAN128, κωδικός 39, κωδικός 39 πλήρης ASCII, κωδικός 39 τριποπικός, κωδικός 128, κωδικός 128 πλήρης ASCII, codabar, διαστρωματωμένος 2 από 5, διακριτός 2 από 5, κωδικός 93, MSI , κωδικός 11, ATA, παραλλαγές RSS, κινέζικα 2 από 5 ...
Φυσικά χαρακτηριστικά	
Υποστηριζόμενες διεπαφές:	PS2, RS232, USB
Τάση:	DC + 5V +/- 5%
Ρεύμα:	100 mA
Ανενεργό ρεύμα:	<40 mA
Πηγή ενέργειας:	Ισχύς κεντρικού υπολογιστή ή εξωτερική τροφοδοσία (RS232)
Γωνία σάρωσης	Κλίση 45 ° Ανύψωση 60 °
Διαστάσεις:	L165mm X W63mm X H87mm
Βάρος:	129 γραμ. (Χωρίς βάση)
Στάση	Προαιρετικός
Χρώμα:	Γκρι και μαύρο
Περιβάλλον χρήστη	
Θερμοκρασία λειτουργίας:	0 °C ~ 40 °C
Θερμοκρασία αποθήκευσης:	-40 °C ~ 60 °C
Υγρασία:	5 ~ 95% σχετική υγρασία, χωρίς συμπύκνωση
Ηλεκτροστατική εκφόρτιση:	Επιβεβαιώστε την +/- 15KV απαλλαγή αέρα και +/- 8KV από την απαλλαγή επαφής
Προδιαγραφές πτώσης:	Αντέχει πολλές σταγόνες 1,5 m στο σκυρόδεμα
Ασφαλής:	
EMI / RFI:	FCC Class A και CE
Ασφάλεια λέιζερ:	Προϊόν λέιζερ CDRH κατηγορίας 2

Λεπτομέρειες προϊόντος:



ocom
All your side

*Handheld Laser
Barcode Scanner*

OCBS-LA11

Product Picture





Features

Simple but not easy

Handheld laser barcode scanner with auto sense function;



Flexible operation with 360 degree



rotation metal stand;



High scan rate (100 scans/sec) and long reading distance;



Excellent decode capability;



KBW, RS232 and USB supported;



||| All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance:	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	30%, minimum reflective difference (@650nm)
Error Rate:	1/3000000
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...

Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165mm X W63mm X H87mm
Weight:	129g (without stand)
Stand	Optional
Color:	Grey and black
User Environment	
Operating Temperature:	0°C~40°C
Storage Temperature:	-40°C~ 60°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port

5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.





Monica Fu



OCOM Technologies Limited

Add: 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Tel: 0086.755.8605.3207 ext 801

Fax: 0086.755.8605.3207 ext 868

Web: www.ocominc.com

E-mail: sales01@ocominc.com, sales01@ocomtech.com.cn

Skype: ocomsales01; **MSN:** ocomsales01@hotmail.com

Ali TM: cn1001868228; **QQ:** 1483705401

Mobile/Wechat/Whatsapp: 0086.189 4871 3992



Reliable One-Stop Supplier for POS and Auto-ID Related Products