

Υψηλή τραχιά 433Mhz 2d barcode σαρωτή με Ράφια παλέτας

Μοντέλο: OCBS-W231-4/B

Χαρακτηριστικά γνωρίσματα:

- 1, 433Mhz Wireless απόσταση επικοινωνίας εξωτερική 300m, εσωτερική 100m? Απόσταση ασύρματης επικοινωνίας Bluetooth εξωτερική 20m και 10m σε εσωτερικό χώρο?
- 2, εξοπλισμένο με την επικοινωνία και την βάση φόρτισης
- 3, μαλακό πλαστικό κάλυμμα για προστασία του φακού και διάρθρωσης σημαντικά βελτιώνει την απόδοση του αντι-drop?
- 4, Barcode οθόνη υπολογιστών και κινητών τηλεφώνων μπορούν να σαρωθούν?
- 5, δεν χρειάζεται οδηγού, τοποθέτησης και άμεσης λειτουργίας?
- 6, μπορεί να αποθηκεύσει περισσότερα από 10.000 κομμάτια των δεδομένων.
- 7, πολλαπλές σαρωτές μπορεί να συνδεθεί σε ένας δέκτης (433mhz).

Παράμετροι:

Με στόχο την πηγή φωτός	617 nm LED
Πηγή φωτός φωτισμού	625 nm LED
Γωνία ανίχνευσης	39° (H) x 25 ° (V)
Γωνία περιστροφής	0 - 360°
Γωνίας ανύψωσης	65° ±
Γωνία κλίσης	± 60°
Αντίθεση εκτύπωσης	Υψηλότερο από 25%
1D	UPC/EAN, UPC/EAN με supplementals, BooklandEAN, ISSN, UCC κουπόνι επεκταθεί, Code128, GS1-128, ISBT 128, Κωδικός 39, κώδικας 39 πλήρη ASCII, Trioptic Κωδικός 39, κώδικα 32, κώδικα 93, Code11, Matrix 2 από 5, Interleaved 2 από 5, διακριτά 2τουπαραρτήματος 5, Codabar, MSI, κινεζική 2 5, Barvariants δεδομένων GS1, Κορεατικά 3 5, ISBT Concat
2D	PDF417, MicroPDF417, σύνθετα κώδικες, TLC-39, δεδομένα μήτρα, Maxicode, QR Code, MicroQR, των Αζτέκων
Διεπαφή	USB (καλώδιο δέκτη Wireless)
Απόσταση επικοινωνίας	433mhz: μέσα: 100m? Εξωτερικά: 300m (μέγ.) Bluetooth: Εσωτερικό: 10m Εξωτερικό: 20 m (μέγ.)
Θερμοκρασία λειτουργίας	-10 βαθμοί C - 45 βαθμοί C
Θερμοκρασία αποθήκευσης	-20 deg C - 65 βαθμοί C
Υγρασία λειτουργίας	5% - 85%
Υγρασία αποθήκευσης	5% - 95%
Ανθεκτικότητα	Αντέχει σε πολλές σταγόνες 1,5 m στο σκυρόδεμα
Ισχύς εισόδου	Συνεχές ρεύμα 5V, 280mA
Χρόνος φόρτισης	6h
Μπαταρία	1500mAh
Φωτεινότητα	Εσωτερικό: 3.000 LUX max? Έξω από το ηλιακό φως: 86000 LUX max
Βαθμός IP	IP42
ΑΠΟΚΩΔΙΚΟΠΟΙΗΣΗ ΣΕΙΡΈΣ	

Τυπική απόδοση *		Χαρακτηριστικές περιοχές εργασίας	
		Εύρος εστίασης HD	
Bar Code τύπου	Σύμβολο πυκνότητα	Κοντά σε:	Τώρα
Κωδικός 39	5.0 mil	5mm	90mm
UPCA 100%	13,0 mil	8mm	200mm
Κωδικός 39	20,0 mil	8mm	250mm
PDF 417	6,8 mil	5mm	95mm
Πίνακας δεδομένων	10.0 mil	5mm	110mm
QR Code	20,0 mil	10mm	150mm
Ανάλυση κώδικα 1D 39	4 mil		
Ψήφισμα δεδομένα 2D Matrix	10 mil		
Υλικό	ABS + PC		
Διάσταση	Base(145*112*74mm) σαρωτή (70 * 95 * 168 χιλ.)		
Καθαρό βάρος	Βάση 185g σαρωτή 186 γραμμάρια		
Πληροφορίες για την παραγγελία:	OCBS-W231-4: 433mhz ασύρματο 2d barcode σαρωτή με λίκνο		
	OCBS-W231-B: Bluetooth 2d barocde σαρωτή με βάση		



FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

1

FAST SCAN,HIGH RECOGNITION RATE



2

STRONG DECODING ABILITY



3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION



4

STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE



5

NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

It's APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



**PRODUCT
INORMATION**

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wireless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base (145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.



Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: [ocomsales15](#);

Whatsapp: +0086.189.4879.9080;

www.ocominc.com

www.ocominc.com