Mini Portable 58mm Bluetooth Thermal Printer
(Model Number: OCPP - M09)

This mini printer with model number OCPP -M09 is a Android (or IOS+ Android) ,Window, Linux, JAVA compatible battery powered 58mm portable mobile thermal pos printer which combines USB and Bluetooth (optional) communication ways together. This printer could be powered by επαναφορτιζόμενη μπαταρία, power adapter, or car charger (depending on specified models) . Special model can connect with 8 smart devices for printing at same time. We have CE, FCC and other required certifications.

Χαρακτηριστικά:

- Mini size suitable for portable application;
- Windows, Java, Linux, Android (or Android +IOS) operation system supported;
- Bluetooth και USB communication supported;
- SDK for Android available;
- 1D, 2D barcode (QR code), and image printing supported;
- Can change the printer name, password, baud rate online;
- One printer can connected with up to 8 smart devices (7 Android, one Apple device) visa blue tooth;
- Low power consumption and large capacity Lithium battery (1500mAh), 4~5 days standby;
- Powered by επαναφορτιζόμενη μπαταρία, power adapter, or car charger (specified models)
- Higher print speed 70mm/sec;
- 100km thermal printer head life;
- Multiple languages supported;
- ESC/ POS command set compatible;

Προσδιορισμός:

Overall Dimension (W×D×H)	105×75×45mm
Βάρος	134g
Χρώμα	Μαύρος
Print method	Thermal line printing
Print commands	ESC/ POS compatible command set
Effective print width	48mm
Print speed	Up to 70mm/sec
Ανάλυση	8 dots/mm(203dpi)
Print font	12x24/ 24x24
Column capacity	32 columns/ 16columns
Character size	1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)
Paper dimensions	58.0±0.1mm x diameter 40.0mm
Paper thickness	0.06 to 0.08mm
Σετ χαρακτήρα	Alphanumeric/ Chinese Kanji
Διεπαφή	USB, Bluetooth (optional)
Λάμψη	256KB
Power Adapter	5V DC/2A
Battery Power	7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper
Αλλα χαρακτηριστικά	Paper detection, manual shut down
Συνθήκες εργασίας	Temperature:-10~50 degC, Humidity:10%~90%
Ονομα της συσκευής	Can be customized, letter and digital for option, at max 30 ASCII characters.

Κωδικός πρόσβασης	Enter default pairing code “1234”, it can be customized or change by customer itself. At max 6 digitals.
Power plug dimension	3.5*1.1mm

ocom®
At your side
OCPP-M09
FEED
ISO
FC
CE
RoHS

ocom®
At your side
OCPP-M09
ocom
At your side
ERROR CHARGE
FEED
ISO FC CE RoHS

OCOM®

At your side

OCPP-M09

ISO FC CE RoHS

Ocom®
At your side

OCPP-M09