

15.6 or 15.1 Inch All In One Touch POS Terminal

(M/N: POS -H156W/A-H151W/A)



OCOM H series pos integrated high speed thermal printer and scanner module inside, it is a kind of cost-effective machine for using, different frame colors make machine more beautiful, extended IO interface make a few more external devices connected, newly designed rear cover which can be easily removed without tools for faster installation and maintenance.

Χαρακτηριστικά:

Intel Celeron Series e Intel Core I3 I5 Processore per opzione

Processore RK3288 ad alta velocità RockChip

EMMC 8 GB / 16 GB / 32 GB per opzione

Driver hard msata SSD 64GB, SSD 128GB un 256 GB per opzione

Stampante termica ad alta velocità da 58 mm e 80 mm integrata per opzione

Pannello tattile capacitivo proiettato multi-punto

Lato opzionale MSR e VFD220 visualizzano il display del cliente montato sul coperchio pos teriore

Scanner per bar-codici integrato per opzione

Display SureFace TRUE e ACQUA / RESISTENTE RESISTENTE RESISTENTE

Προδιαγραφές:

Πρότυπο		POS -H156	POS -H151
Όνομα		15.6 inch all in one touch screen pos terminal	15.1 inch all in one touch screen pos terminal
Κατάλυμα		plastic with metal combined	
Χρώμα		white machine body or black machine body match orange or blue frame colors	
Οθόνη			
Κύρια οθόνη		15.6 inch touch screen monitor	Monitor touch screen da 15.1 pollici
Ανάλυση		1366*768	1024 * 768.
Λάμψη		250cd / M. ² .	
Vista ad angolo		Horizon: 150; Vertical :140	
Οθόνη αφής		Tocco capacitivo di G + G del multi-punto	
Sotto-es posizione		15.6/14/11.6 inch display W/ or W/o touch function, resolution 1366*768 for optional	15.1 inch display W/ or W/o touch function, resolution 1024*768
Visualizzazione del cliente		2*20 VFD mounted to back cover for option	
εκτέλεση			
Windows J1900	Μητρική πλακέτα	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4 th . CPU di generazione per opzione	
	Μεμoρια di sistema	1*SO-DIMM DDRIII slot, support1333*/1600 2GB/4GB/8GB for option	
	Dis pos itivo di archiviazione	Msata SSD 64 GB o Higer, fino a 256 GB	
	Audio	On board Real Tek ALC662 audio chip	
	LAN	10 / 100mbs, Realtek RTL8111F LAN Chip Slot mini PCI-E integrato, supporto Modulo WiFi incorporato	
	Λειτουργικό σύστημα	Windows7/8/10, Embedded,WE POS ,Linux	

Android RK3288	Μητρική πλακέτα	Rockchip series RK3288 ,quad core 1.8G, RK3399 for optional
	Memoria di sistema	On board DDRIII 2GB,4GB for option
	Dis pos itivo di archiviazione	On board 16GB EMMC,32GB for option
	Audio	On board Real Tek ALC5640 audio chip
	LAN	10 / 100mbs, Realtek RTL8111F LAN Chip
	WIFI&BT module	Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support
	Λειτουργικό σύστημα	Android 7.1
Connettività		
Windows/Android(J1900&RK3288)	Pulsante di accensione * 1	
	12V DC in Jack * 1	
	LAN: RJ-45 * 1	
	USB *6	
	MIC in*1, Audio out*1	
Windows(J1900)	COM(RS232) *1 or HDMI*1 for option	
	VGA(15Pin D-sub)*1	
	RJ11 for Cash drawer *1 for option	
Android(RK3288)	COM(RS232) *1	
	On board RJ11 for Cash drawer *1 ,RJ11 from printer port for cash drawer*1(optional)	
	TF card slot*1	
Opzioni		
80mm thermal printer	direct thermal printing	
	100mm/s printing speed	
	79.5-/+ 0.5mm paper width and printable width 72mm	
	with auto cutter function and thermal head life 50km	
	LPT communication	
58mm thermal printer	direct thermal printing	
	85mm/s printing speed	
	57.5-/+ 0.5mm paper width and printable width 48mm	
	thermal head life 50km	
	LPT communication	
Msr.	lato opzionale MSR.	
web camera	web camera mounted on top of the display for option	

Ερευνητής	support 1D&2D code-scanning for option
Ομιλητής	4ohm/5w speakers inside for option
Πακέτο	πακέτο
Βάρος	net□5.6Kg , gross:7.7Kg for 15.6 with15.6 dual screen /no printer built in
Confezione con schiuma dentro	340*450*480mm
2in1 carton	700*460*500mm /gross□17Kg
περιβάλλον	
Θερμοκρασία λειτουργίας	0 a 40 gradi centigradi
Θερμοκρασία αποθήκευσης	-10 a 60 gradi centigradi
Umidità lavorativa	10%~80%
Umidità di stoccaggio	10%~90%
αξεσουάρ	
Adattatore di alimentazione	110-240V / 50-60Hz AC PowerInput, προσαρμογέας εξόδου DC12 / 5A για τον εκτυπωτή W / O και μηχανή εκτυπωτή W / 58mm DC12V / 7A Έξοδος προσαρμογέα μόνο για μηχανή εκτυπωτή W / 80mm
Καλώδιο τροφοδοσίας	Βύσμα καλωδίου τροφοδοσίας συμβατό με ΗΠΑ / EU / UK κ.λπ. Και προσαρμοσμένη
Οδηγός CD	Οδηγός μητρικής πλακέτας και οδηγούς αφής μέσα για την επιλογή
Άλλα	
Συμμόρφωση	FCC Class A / CE / LVD / LVD / CCC

Περισσότερες εικόνες των προϊόντων που εμφανίζονται



Δεν χρειάζεται εργαλεία για την κατάργηση του καλύμματος pos Temester, πολύ άνετα για την ενημέρωση του RAM / SSD και της συντήρησης πελατών



Οι πλευρικές θύρες USB κάνουν το μηχάνημα να ανεβάζει πιο εύκολα και να εκφορτώσει



Πόρτες Εξωτερικές



Πακέτο

