

MHz Ασύρματη RF433 Φορητό απολογισμός Terminal Βιομηχανική PDA (Μοντέλο: OCBs-D007)

Προδιαγραφή:

| | |
|-----------------------------|--|
| Χαρακτηριστικά απόδοσης | |
| Πηγή φωτός | 650nm λείζερ |
| Σάρωση Μοντέλο | Ενιαία γραμμή |
| Σάρωση πλάτος & amp? πεδίο | 220 χιλιοστά / 0 ~ 250 χιλιοστά (0,33 χιλιοστά, PCS 90%) |
| Διασύνδεση | Τυποποιημένη διαμόρφωση μίνι δέκτη USB? RS232 και PS2 προαιρετικό |
| Σάρωση ποσοστό | 48 ± 2 σάρωση / δευτερόλεπτο |
| Error Rate | 1 / 5.000.000 |
| Τον τρόπο της δουλειάς | προκληθεί ή αυτόματο (συνεχής λειτουργία) σάρωσης |
| Σάρωση γωνία | Pitch 30 ° / Roll 65 ° / Yaw 55 ° |
| Υποστηριζόμενα barcodes | EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN128, Codabar, Industoal 2μ 5, Interleave 2of5, Matrix 2of5, MSI κ.α. |
| Δείκτης | Βομβητή, οθόνη LCD |
| Φυσικά Χαρακτηριστικά | |
| Οθόνη | 2,8 ιντσών, 10 * 10 γραμμές? Ψήφισμα: 320 * 240 |
| Διαστάσεις | Τερματικό: 160x68x29mm? Δέκτης: 52x20x10mm |
| Υλικό | ABS + διοξείδιο του πυριτίου |
| RAM | 16M |
| Χρώμα | Μαύρο ή γκρι |
| Χαρακτηριστικά επικοινωνίας | |
| Συχνότητα | 433 |
| Διαμόρφωση | GFSK |
| Απόσταση μετάδοσης | Οπτική ευθεία απόσταση 300 μέτρων (Max) |
| Ρυθμός μετάδοσης | 200kbps |
| Ηλεκτρικά Χαρακτηριστικά | |
| Μπαταρία | Li-μπαταρία (3.7V, 2800mAh) |
| EMI / RFI: | CE & amp? Συμμόρφωση με την FCC DOC |
| Τρέχουσα Εργασίας | 50mA |
| Περιβάλλον | |
| Θερμοκρασία Λειτουργίας | 0 βαθμός Γ ~ 45 βαθμούς C |
| Θερμοκρασία αποθήκευσης | -20 Βαθμών Κελσίου ~ 60 βαθμούς C |
| σχετική υγρασία | 5% ~ 95% (χωρίς συμπύκνωση) |
| φωτεινότητα | Max 5,000Lux |
| Πληροφορίες παραγγελίας | |
| OCBs-D007 | 433 Ασύρματο Φορητό Τερματικό απογραφής |
| OCBs-D107 | Καλώδιο USB Φορητό απογραφής Terminal |

Λεπτομέρειες προϊόντος:



**Wireless/USB Cable
Portable Stocktaking Terminal
OCBS-D007/OCBS-D107**



Product Picture



Features

Simple but not easy

2.8" color display, menu with image for easy operation;



Wireless Version: wireless and storage technology, no restriction of distance;

2800mA super capacity battery
ensures long working time;



Support automatically matches products
and show product name after scanned
the barcode;



Suitable for overall process of the commodity
circulation including receiving, shipping,
stocktaking, loss report, replenishment etc;





All-round show



Application Area

Commercial: handheld mobile POS, chains / stores / counters data acquisition, shoes ordering, card management, bill management

Commonality: mobile government, mobile police, population information management, postal management, library management

Logistics: warehouse management, product traceability, picking medicine distribution, logistics and express, logistics and distribution

Industry: production process management, forestry data collection, three meter reading, fixed asset management,



Parameter

| Performance Characteristics | |
|-----------------------------|--|
| Light source | 650nm laser |
| Scan Model | Single line |
| Scan width & field | 220mm/0~250mm (0.33mm, PCS 90%) |
| Interface | Standard configuration mini USB receiver, RS232 and PS2 optional |
| Scan rate | 48±2 scan/second |
| Error Rate | 1/5,000,000 |
| Working way | triggered or automatic (continuous mode) scanning |

| | |
|--------------------------------------|---|
| Scan angle | Pitch 30°/ Roll 65°/Yaw 55° |
| Supported barcodes | EAN-8,EAN-13,UPC-A,UPC-E,Code 39,Code 93,Code 128,EAN128,Codabar,Industial 2of5,Interleave 2of5,Matrix 2of5, MSI etc. |
| Indicator | Beeper, LCD display |
| Physical Characteristics | |
| Screen | 2.8 inch, 10*10 lines; resolution: 320*240 |
| Dimensions | Terminal: 160x68x29mm; Receiver: 52x20x10mm |
| Material | ABS+ silica |
| RAM | 16M |
| Color | Black or Grey |
| Communication Characteristics | |
| Frequency | 433MHZ |
| Modulation | GFSK |
| Transmission Distance | Visual straight line distance 300 meters (Max) |
| Transmission rate | 200Kbps |
| Electric Characteristic | |
| Battery | Li-Battery (3.7V, 2800mAh) |
| EMI/RFI: | CE&FCC DOC compliance |
| Working Current | 50mA |
| Environment | |
| Operation Temperature | 0 Degree C~45 Degree C |
| Storage Temperature | -20 Degree C ~60 Degree C |
| relative humidity | 5%~95% (non- condensing) |
| ambient brightness | Max 5,000Lux |
| Ordering Information | |
| OCBS-D007 | 433MHZ Wireless Portable Stocktaking Terminal |
| OCBS-D107 | USB Cable Portable Stocktaking Terminal |

Production Line





Capacity

| Verified | Product Name | Production Line Capacity | Actual Units Produced(Previous Year) |
|----------|---------------------------------|--------------------------|--------------------------------------|
| ✓ | Thermal Printer | 40,000 Sets / Month | 250,000 Sets |
| ✓ | Dot Matrix Printer | 15,000 Sets / Month | 10,000 Sets |
| ✓ | Bluetooth Printer | 30,000 Sets / Month | 20,000 Sets |
| ✓ | Barcode Scanner | 40,000 Sets / Month | 20,000 Sets |
| ✓ | POS Machine | 5,000 Sets / Month | 10,000 Sets |
| ✓ | Magnetic Card Reader and Writer | 45,000 Sets / Month | 50,000 Sets |

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

| Verified | Machine Name | Brand & Model No. | Quantity |
|----------|--------------------------|-------------------|----------|
| ✓ | Ageing Tester | No Information | 6 |
| ✓ | Withstand Voltage Tester | CC2670A | 1 |
| ✓ | Oscilloscope | TBS1102 | 1 |
| ✓ | DC Power Supply | PS-305DM | 6 |
| ✓ | Digital Torque Meter | HP100 | 1 |
| ✓ | Calliper | GUANGLU | 2 |
| ✓ | Multi-meter | VC890D | 7 |
| ✓ | Test Computer | No Information | 13 |

Certifications



Packing and Shipment



Payment





Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?



Company Profile

**This Assessed Supplier Has Been
Independently Verified**

Build Your Growth On Trust



TÜV Rheinland®





FOVHemana
Precisely Right.



OCOM Technologies Limited, founded in 2007, is one of the leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and are hot selling in Europe, Australia, Asia, and other areas.



OCOM has a professional team including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years. All of the sales have more than 5 years' experience, which helps us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like to establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

 Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,
Shenzhen 518054, China;

Websites: <http://www.possolution.com.cn> ; <http://www.ocominc.com> ;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: [ocominc2000](#), [ocominc](#);

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: [szocominc](#), [cn1500439666](#);

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



Σχετικά έγγραφα:

Θέλετε να μάθετε περισσότερα inf προϊόνormation; Παρακαλώ Κανε κλικ εδώ. 

[Προσδιορισμός](#)

[Εγχειρίδιο Χρήσης](#)

[OCBs-D007 64bits οδήγησης δέκτη](#)

[OCBs-D007 32bits οδήγησης δέκτη](#)

[OCBs-D007 εφαρμογής PC](#)

[OCBs-D007 SDK \(DLL2.0\)](#)