thermal label printer machine for sticker （OCBP-007）

sticker printer,
label printer machine ,
thermal printer.

Features:

High quality double-walled clamshell design

32-bit RISC CPU

8MB SDRAM,4MB Flash

Head-up sensor

203 dpi resolution

102mm(4'''')/s high printing speed

108mm printing width

20-112mm (0.78”-4.4”)adjustable media width

Specification:

Parameter	
Resolution	8 dots/mm(203DPI)
Printing method	Direct Thermal
Max.print speed	102 mm (4”)/S
Max.print width	108 mm (4.25”)
Max.print length	2286 mm (90”)
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	20-112mm (0.78”-4.4”)
Media thickness	0.06~0.16mm((2.36~6.3mil)
Label length	10~2,286mm(0.4''''~90'''')
Label roll capacity	127 mm (5“) OD (outside wound)
Enclosure	Double-walled plastic
Physical dimension	240 mm（W）× 211 mm（H）× 166 mm （D）
Weight	2.15kg
Processor	32-bit RISC CPU
Memory	4MB Flash Memory, 8MB SDRAM, SD card reader for Flash memory expansion, up to 4 GB
Interface	USB 2.0
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
Barcode	1D bar code：Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
	2D bar code：PDF-417, Maxicode, DataMatrix, QR code
Font and barcode rotation	0°、90°、180°、270°
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing, Storage: -40 ~ 60°C, 10 ~ 90% non-condensing

Product Description: