

(OCPP-80K)Barcode Thermal Printer 58 Mm No Ink Portable Printer Wifi Square Thermal Printer

(M/N:OCPP-80K)



Features:

It can be used as top paper coming printer and front paper coming printer
It's built-in power adaptor, which avoids messy cords everywhere, saving much space

Support 8 kinds abundant interface combination

Supports multi 1D barcode and QR code printing

Support printer status monitoring function

Support printing queuing ticket function

100M Ethernet port, ultra high speed data transmission

256KB NV Logo storage and 256kb big buffer memory

48 or 80mm adjustable paper separator for option

100KM long life printer head

Specifications:

General	
Model	OCPP-80K
Name	80mm desktop thermal printer with auto cutter
Color	Black
Interface	255 USB+LAN+USB+BT/USB+WIFI(URL+WIFI+URL+BT+USB+RS232)
Power supply	Input:AC 100V-240V 50-60Hz,Output:DC 24V/2.5A
Cash drawer	DC 24V/1A
Graphics printing	Supports bitmap download and print (each bitmap size Max.20K)
Printer head lifespan	100KM
Cutter	Auto cutter
Sensors	Paper out, cover open, cutter jam,paper jam and black mark detection(Optional)
Buffer	Input buffer:256K/NV Flash 256K
Accessories	Data cable,power adaptor,power cord,paper roller,CD,manual, Paper separator(optional)
OS supporting	Compatible with IOS/ Android/ Windows
Safety standards	CE, FCC, RoHS etc.
Printing capability	
Printing method	Direct Thermal line
Resolution	576 Dots/Line or 512 Dots/Line(8dots/mm,203dpi)
Printing speed	200mm/s (U+R) 260mm/s (U+L+U+BT/ U+WIFI) 300mm/s (U+R/ U+L+BT/ U+L+WIFI)
Print width	72mm
Graphics printing	Supports bitmap download and print
Printing Command	Compatible with ESC/POS
Barcode and character	
Barcode	ID barcode: UPC-A/EPC8/JAN13/EAN13/JAN8/EAN8/COE9/ITF/ CODABAR/CODE93/CODE128 2D barcode:QR CODE/Single USB or UR solution no QR code function
Character	Standard GB18030 simplified / traditional Chinese Fonts
Character size	88dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm Font: B: 9*17dots, 1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Japanese/Korea	Optional
User-defined language	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/iran/WPC1252/PC866/PC852/PC858/iran/Latvian/Arabic/PT151,1251/WPC737/WPC1257/Thai/Vietnam/PC864/PC1001/Latvian/PC1001/PT151,1251/WPC1257/PC864/(Vietnam)/(Thai)
Media	
Paper type	Thermal roll paper
Paper width	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper thickness	0.06~0.08mm
Paper roll diameter	83mm Max
Paper separator	Optional
Physical	
Dimension	186*145*135mm
Weight	1.65kg
Package box	300*190*180 mm
12 in 1 carton	615*370*535mm/21.5kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	20 to 60 degrees centigrade, 10%~90% No condensation

Product details:

