

Best price 58mm receipt thermal printer with USB RS232 Parallel LAN optional ports (Model: OCPP-586)

Specification:

| | |
|---------------------|---|
| Printing Method | Direct thermal |
| Print Density | 384dots/line (203DPI) |
| Character Size | 384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm |
| Barcode Type | JAN13□EAN13□JAN8□EAN8□CODE39 |
| Printing Command | Compatible with EPSON ESC/POS |
| Language | OEM437/Katakana/OEM850/OEM860/OEM863/OEM865/West Europe/ Greek/Hebrew/East Europe/Iran/WPC1252/OEM866/OEM852/ OEM858/IranII/Latvian/ Arabic/PT151,1251/OEM747/ WPC1257/Vietnam/OEM864/Hebrew/WPC1255/Thai |
| Printing Speed | 90mm/sec |
| Paper Width | 57.5±0.5mm |
| Paper Thickness | 0.06-0.08mm |
| MCBF(life) | 50km |
| Dimension | 190*132*119mm |
| Gross Weight | 1.2KG |
| Auto Cutter | manual cutter |
| Sensor | Paper Near End Sensor, Paper End Sensor, Cover open sensor |
| Roll Paper | Φ75mm |
| Interface | RS-232C, Parallel, USB, LAN |
| Driver | Win 9X, Win 2000, Win 2003, Win XP, Win Vista, Win 7 compatible with ESPON |
| Printer Supply | DC12V/3A |
| Cash Drawer Control | DC12V/1A |
| Working Temperature | 0-45°C, Humidity: 10-80% |
| Saving Temperature | -10-60°C, Humidity: 10-90% |

Product Details:



Relevant documents:

Do you want to know more product information?Please Click here.

- Specification
- User's Manual
- Driver