

58MM Portable Bluetooth Thermal Printer Android Support Thermal Printer

Features:

Support Windows, Java, Android

Bluetooth, USB Port

Higher print speed 90mm/sec.

100km TPH Life.

Low power consumption and large capacity Lithium battery.

Specification:

Overall Dimension (W×D×H)	105×75×45mm
Weight	134g
Color	Black
Effective print width	48mm
Print method	Thermal line printing
Print commands	ESC/POS compatible command set
Print speed	Up to 90mm/sec
Resolution	8 dots/mm(203dpi)
Print font	12x24/ 24x24
Column capacity	32 columns/ 16columns
Character size	1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)
Paper dimensions	58.0±0.1mm x diameter 40.0mm
Paper thickness	0.06 to 0.08mm
Character set	Alphanumeric/ Chinese Kanji
Interface	USB, Bluetooth
Data buffer	Up to 5K bytes
Power Adapter	9V DC/2A
Battery Power	7.4V DC/ 1500mA; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper
Other features	Paper detection, power detection, Manual shut down
Working conditions	Temperature:-10-50Degree, Humidity:10%-90%
Storage conditions	Temperature:-20-70Degree, Humidity:5%-95%
Device name	Can be customized, letter and digital for option, at max 30 ASCII characters.
Password	Enter default pairing code "1234", it can be customized. At max 6 digitals.
Power plug dimension	3.5*1.1mm



58mm Bluetooth Thermal Printer for Andorid or IOS system

OCPP-M03



Product Picture





Features

Simple but not easy

Battery charge indicator, easy to know rest power.



Higher print speed 90mm/sec



Support Windows,Android, or iPhone OS;
Bluetooth, USB and RS232 communication



Higher print speed 90mm/sec.
100km TPH Life



Low power consumption and large capacity Lithium battery.



All-round show





Application Area

Bus/Taxi receipt, Traffic Citation, Logistics, Transportation,
Warehouse management, Delivery, Illegal Parking Ticket,
Drugstore, Food delivery, restaurant, Price Tag, Retail/Farm



Parameter

Overall Dimension (W×D×H)	105×75×45mm
Weight	134g
Color	Black
Effective print width	48mm
Print method	Thermal line printing
Print commands	ESC/POS compatible command set
Print speed	Up to 90mm/sec
Resolution	8 dots/mm(203dpi)
Print font	12x24/ 24x24
Column capacity	32 columns/ 16columns
Character size	1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)
Paper dimensions	58.0±0.1mm x diameter 40.0mm
Paper thickness	0.06 to 0.08mm
Character set	Alphanumeric/ Chinese Kanji
Interface	USB, RS-232, Bluetooth (optional)
Flash	256KB
Power Adapter	9V DC/2A

Paper Roll Installation



- A Open the printer cover.
- B Install the roller in the roll paper, and put them into the printer.
- C Pull out some paper outside the printer and then close the printer cover.
- D Close the top cover. Press the printer cover to avoid error position of roll paper.
- E Tear-off the paper correctly.

Shipping and payment

1. EXPRESS: around 3-7 working days to arrive
2. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
3. By sea: depend on which destination port
4. T/T
5. Western Union
6. Escrow
7. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.

