

# Cheap USB 58mm mini pos thermal receipt printer

(OCPP -58E)

## Product Introduction:

OCPP -58E is a well-designed economic printer for common thermal bill printing, this model is with solid material, Exquisite workmanship. Transparent cover design, simple and fashion, easy for users to know the paper rolls' Using status, OCPP -58E adopt built-in Power supply, not only can save space, but also easy for users to configure and use the printers. It's a very good choice for economical printing.

## Product Features:

- Simple and fashion, With solid material, exquisite workmanship.
- Easy paper install structure, simple and convenient to operate
- Built-in power supply design, to save space and more convenient to configure;
- Transparent cover design, the user can know the paper roll's using status anytime;
- Support GB18030 big font, easy to print uncommon characters
- Support multi language print, suitable for users all over the world;
- Support download and print LOGO & graphics ;
- Support Windows, Linux, Android and IOS system printing

## Application Area:

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, pos terminal

## Parameters:

| Items                    | Parameters             |   |
|--------------------------|------------------------|---|
| Print parameters         | Printing Method        | Thermal Line  |
|                          | Printing Width         | 48MM  |
|                          | Resolution             | 384dots/Line(8dots/mm,203dpi)   |
|                          | Printing Speed         | 90mm/Second   |
|                          | Interface Type         | USB,USB+Bluetooth   |
|                          | Line Spacing           | 3.75 mm(Can adjust line spacing by command)   |
|                          | Line No.               | Font A:32 character /Line<br>Font B: 42 character/Line<br>Simple,traditional Chinese-16 lines   |
| Bar code character       | Character              | Standard GB18030 simplified / traditional Chinese Fonts   |
|                          | Character Size         | ANKcharacter,Font A:1.5×3.0mm(12×24dots)<br>Font B:1.1×2.1mm(9×17dots) Simplified/Traditional Chinese:3.0×3.0mm (24×24 dots)  |
|                          | Extended character set | PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151.1251/PC737/WPC/1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151.1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai) |
|                          | Bar code               | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128  |
| Graphics printing        | Graphics printing      | Supports bitmap download and print  |
| Paper                    | Type                   | Thermal Roll  |
|                          | Width                  | 57.5±0.5mm  |
|                          | Diameter               | ≤60mm   |
|                          | Feed Method            | Easy feed (Clamshell feed)  |
| Print commands           | Commands               | ESC/ POS  |
|                          | Power Adaptor          | Input:AC 100V-240V, 50-60Hz<br>Output:DC 12V/2A   |
|                          | Casher Drawer output   | DC 12V/1A   |
| Buffer                   | Input Buffer           | 4K  |
|                          | NV Flash               | 40K   |
| Physical characteristics | Weight                 | 590g  |
|                          | Dimension              | 185*130*112(MM)   |
| Environment              | Working                | Temp:5 ~ 45 ° C, Humidity:10 ~ 80%  |
|                          | Storage                | Temp:-10 ~ 50 ° C, Humidity:10 ~ 90%(No dew)  |
| Reliability parameter    | Print Head Life        | 50KM(Print density≤12.5)  |

## Relevant documents:

[Driver and CD files](#)