

## China Factory Price 76mm Impact Dot Matrix Receipt Printer with Auto-cutter

□M/N:OCP-763□

### Feature:

- 76MM impact dot matrix receipt printer with automatic cutter;
- Compatible with EPSON;
- With Black mark detection function;
- Multiple interfaces available: Serial /parallel/USB/LAN;
- Support cash drawer kick out;
- Easy operation and elegant appearance.

### Specifications:

|                                                                                                                       |                                                                                       |
|-----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Printing method                                                                                                       | 9 pins serial dot matrix                                                              |
| Print font                                                                                                            | FONT A: 33 or 35; FONT B: 40 or 42                                                    |
| Column capacity                                                                                                       | 400dots                                                                               |
| Character size                                                                                                        | ANK, Font A:9*9dots, Font B:7*9dots Simplified Chinese, traditional Chinese:16*16dots |
| Character set                                                                                                         | Buyer option                                                                          |
| Character per line                                                                                                    | 400dots                                                                               |
| Printing speed                                                                                                        | 4.5lines/sec                                                                          |
| Receive buffer                                                                                                        | Selectable as 45 bytes or 4k bytes using Dip switches                                 |
| Paper width                                                                                                           | 75.5±0.5mm                                                                            |
| Copy capability                                                                                                       | One original and two copies                                                           |
| Ribbon                                                                                                                | ERC-39                                                                                |
| MCBF(life)                                                                                                            | 10,000,000 lines                                                                      |
| Driver                                                                                                                | Win9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/Linux                       |
| CPU                                                                                                                   | 32 bit                                                                                |
| Storage environment                                                                                                   | Temperature (-10~60°C) humidity (10~90%)                                              |
| Working environment                                                                                                   | Temperature (0~50°C) humidity (10~90%)                                                |
| Dimension                                                                                                             | 230X146X145mm                                                                         |
| Gross weight                                                                                                          | 3.75KG                                                                                |
| Auto cutter                                                                                                           | Yes                                                                                   |
| Paper end sensor                                                                                                      | Yes                                                                                   |
| Paper thickness                                                                                                       | 0.06-0.08mm                                                                           |
| Roll paper                                                                                                            | 75.5±0.5mm* φ65mm                                                                     |
| Interface                                                                                                             | Serial/parallel/USB/ LAN                                                              |
| Command                                                                                                               | Compatible with EPSON                                                                 |
| Cash drawer control                                                                                                   | DC 12-24V/1A                                                                          |
| Power supply                                                                                                          | DC24V/2.5A                                                                            |
| Notes: It uses a highly reliable Japanese print head(SEIKO F347) with a life span rated at more than 10,000,000 lines |                                                                                       |







OCPP-763





OCPP-763



