

China cable bottle waterproof barcode label sticker printer

□Model NO.: OCBP-015□

Features:

Support 8 kinds abundant interface combination

Support TSPL and ECS/POS Command

Supports multi 1D barcode and 2D code printing.

Support printer status monitoring function

100M Ethernet port, ultra high speed data transmission.

2MB big DRAM And 2MB buffer memory.

Standard 25 to 80mm adjustable Paper separator

150KM long life printer head

Technical parameters□

Print Method	Direct Thermal
Command	TSPL and ESC/POS (can change by end user)
Resolution	203dpi ,576dots/line
Printing Width	Max=72mm
Paper Type	Thermal label Paper or continuous receipt Paper
Interface	USB/UR/UL/URL/U+BT/ U+WIFI/URL+BT/URL+WIFI
Print Speed	Max=152mm/s for label, MAX=260mm/s for receipt mode
Paper Width	20mm-80mm
Paper Thickness	0.06~0.19mm
Roll Dia	Max. Ø 83 mm
Paper Cut	Manual tear
DRAM	2MB
Flash	2MB
Font Size	font A:12*24(standard), font B:9*17
Chinese	GB18030,BIG5 24x24dots
Japanese/Korea	Support
User-defined language	PC347(Standard Europe),Katakana,PC850(Multilingual),PC860(Portuguese),PC863(Canadian-French),PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2),PC858,IranII,Latvian,Arabic,PT151(1251) ect.
1D	UPC-A/UPC-E/JAN13□EAN13□JAN8□EAN8□/CODE39/ITF/CODABAR/CODE93/CODE128/MSI/ITF-14/CPOST/PLESSEY,etc.
2D	QR,PDF417, DM
Printing head life	150 KM
Paper separator	Standard
Sensors	Paper out, cover open, cutter jam,paper jam and black mark detection
Input	AC 100V-240V 50/60HZ
Output	DC 24V/2.5A
Working Condition	0°C~45°C, 10%~80%RH
Storage Condition	-10°C-60°C,10%~90%RH

Accessories	Data cable, power adaptor, power code, paper roller, CD, manual, Paper separator (standard)	
Dimensions	196(D)x145(W)x135(H)mm	
Net weight	1.14kg	
Gross weight	1.5kg	
Individual box	Dimension 30X19X18cm(LXWXH)	1unit/carton
Master carton	Dimension 62X36X52cm(LXWXH)	12units/carton
Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS	
SDK	Android, IOS	









OCBP-015





OCBP-015

