

Model	OC-PP-80S
Name	80mm desktop thermal printer with auto cutter
Color	Black
Interface	USB/USB+LAN/USB+BT/USB+WIFI/URL+WIFI/URL+BT
Power supply	Input: AC 100V-240V 50-60Hz Output: DC 24V/2.5A
Cash drawer	DC 24V/1A
Printer head lifespan	150km
Cutter	Auto cutter
Sensors	Paper out, cover open, cutter jam, paper jam and black mark detection (optional)
Accessories	Data cable, power adaptor, power cord, paper roller, CD manual, Paper separator (optional)
OS supported	Compatible with iOS/Android/Windows/Linux
Safety standards	CE, FCC, RoHS, etc.
Printing method	Direct thermal line
Resolution	203 DPI
Printing speed	200mm/s (URL) 240mm/s (URL+BT/URL+WIFI) 300mm/s (URL+BT/URL+WIFI)
Print width	72mm
Graphics printing	Supports bitmap download and print (each bitmap size Max 20K)
Printing Command	Compatible with ESC/POS
Barcode	1D barcode: UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/ CODABAR/CODE93/CODE128 2D barcode:QR CODE/Single USB or QR solution no QR code function
Character size	ANK character, Font: A: 12*14dots, 1.5(W)*3.0(H)mm FontB: 9*11dots, 1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Japanese/Korea	Optional
User-defined language	PC437/Katakana/PC850/PC860/PC863/PC865/West/Europe/Greek/Hebrew/Ext1/Europe/Iran/WPC1252/PC866/PC852/PC858/Tranil/Latvian/Latvian/CPT151_1251/LPC737/WPC1257/Thai/Vietnam/PC864/PC1001/Latvian/PC1001/PT151_1251/WPC1257/PC864/Vietnam/Thai
Media	
Paper type	Thermal roll paper
Paper width	48mm/52mm/54mm/64mm/68mm/76mm/80mm (optional)
Paper thickness	0.06-0.08mm
Paper roll diameter	80mm Max
Paper separator	support
Physicall	
Dimension	180*142*116mm
Weight	1.65kg
Package box	128*123*518mm
8 in carton	475*445*358mm/15.65kg
Working temperature, humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature, humidity	-20 to 60 degrees centigrade, 10%~90% No condensation