

Factory Supply China Factory 58mm Pos Thermal Receipt Printer

(OCP-58X)



#### Product Introduction:

OCP-58X is a well-designed economic printer for common thermal bill printing , It is adopt built-in power supply,not only can save space,but also easy for users to configure and use the printers.It's a very good choice for economical printing.

#### Product Features□

- Simple and fashion,With solid material,exquisite workmanship.
- Easy paper install structure,simple and convenient to operate

- Built-in power supply design, to save space and more convenient to configure;
- Support multi language print, suitable for users all over the world;
- Support download and print LOGO&graphics ;

### Application Area

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

### Parameters

Items	Parameters	
Print parameters	Printing Method	Thermal Line
	Printing Width	48MM
	Resolution	384dots/line(8dots/mm)(203dpi)
	Printing Speed	90mm/Second
	Interface Type	USB/Parallel
	Line Spacing	3.75 mm[Can adjust line spacing by command]
	Line No.	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
Bar code Character	Character	Standard GB2312 simplified Chinese Fonts
	Character Size	ANKcharacter[Font A][1.5×3.0mm][12×24dots] Font B[1.4×2.1mm][9×17dots] Simplified/Traditional Chinese[3.0×3.0mm][24×24 dots]
	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/iran/WPC1252/PC866/PC852/PC858/iranII/Latvian/Arabic/PT151,1251/WPC1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Graphics printing	Bar code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed Method	Easy feed(Clamshell feed)
Print commands	Commands	ESC/POS
	Power Adaptor	InputD/C 100V-240V,50-60Hz OutputD/C 12V/2.6A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	32 KB
	NV Flash	64 KB











