

High quality programmable mobile thermal printer 80mm price cheap

(M/N:OCP-80F)

Feature:

- 1.300mm/s printing high-speed, improve the printing efficiency
- 2.2048K super input buffer, to avoid losing bills
- 3.Support 1D,2D bar code printing
4. Support black mark orientation and re-print
5. Support printer monitoring function, to avoid losing bills;
6. Excellent waterproof, anti - oil, anti-dust structure design
- 7.Movable baffle design, support 80MM,58MM different width of paper roll printing.

Specification:

| Item | Parameters |
|------------------------|--|
| Printing Method | Thermal Line |
| Printing width | 72mm |
| Resolution | 576 Dots/Line or 512 Dots/Line [8dots/mm, 203dpi] |
| Print speed | 300mm/Second |
| Interface | USB+COM+LAN USB USB+LAN+WIFI or USB+BT+WIFI USB+BT |
| Line Spacing | 3.75mm [Can adjust line spacing by command] |
| Line No. | FontA-48Lines/FontB-64Lines/Simple.traditional Chinese-24 lines |
| Character | standard GB18030 simplified / traditional Chinese Fonts |
| Character Size | ANK character:Font A:1.5x3.0mm [12x24 dots] FontB:1.1x2.1mm [9x17 dots] [Simplified/Traditional Chinese:3.0x3.0mm [24x24 dots] |
| Extended character set | PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Iran/Latvian/Arabic/PT151.1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/Latvian/PC1001/(PT151.1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai) |
| Bar code | 1D barcode:UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128 2D barcode:QR CODE |
| Graphics printing | Supports bitmap download and print |
| Cutter Function | Half cut |
| Type | Thermal |
| Width | 79.5±0.5mm |
| Diameter | ≤80mm |
| Feed method | Easy feed(Clameshell feed) |
| Commands | ESC/POS |
| Power Adaptor | Input:AC 110V/220V,50~60Hz Output:DC 24V/2.5A |
| Cash Drawer output | DC 24V/1A |
| Input Buffer | 2048K bytes |
| NV Flash | 256K bytes |
| Weight | 1.2KG |
| Dimension | 186*145*135 |
| Working | Temp:5~45 Centigrade, Humidity:10~80% |
| Storage | Temp:-10 ~ 50 Centigrade, Humidity:10~90%(Nodew) |
| Print Head Life | 100KM(print density LE 12.5) |
| Cutter Life | 1000,000times |
| Driver | Android,IOS, Linux, Win2000, Win2003, WinXP, Win7, Win8, Win8.1 |