

| | |
|-------------------------------------|--|
| Model | OCBS-A200 |
| OS | Android 9 |
| CPU | MTK8768B 2GHz, QuadCore, 12nm |
| MEMORY | 2G RAM+16G ROM |
| Extend Slot | MicroSD, support SDHC, up to 64GB; One micro SIM connector |
| PC Communication | USB 2.0 OTG : Type-C Support TYPE-C Headset |
| Sensors | Light, Proximity, 3D G sensor, Hall |
| LED | Charging, Scan and System status |
| Charging Time | <3.5 hours(Room Temperature) <4 hours(35 °C) |
| Operation Duration | 14 hours |
| Scan Engine | |
| Scan Engine | Datalogic E3200-LE |
| 2D | Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code; EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites |
| 1D | Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes. |
| Post | Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC) |
| NFC(Optional) | 13.56MHz NFC |
| Wireless connectivity | |
| WLAN | 802.11 ac/a/b/g/n |
| WWAN | TDD-LTE (B38/B39/B40/B41) FDD-LTE (B1/B3/B7) UMTS/HSDPA/HSPA/HSPA+ (900/2100 MHz) GSM/EDGE/GPRS (900/1800MHz) |
| VoLTE | LTE CAT6 |
| CA | Downlink 300Mbps, B1/B3/B7/B40/B41 |
| WPAN | BT 4.2/BLE |
| GPS | GPS/A-GPS, GLONASS, Beidou ,Galileo |
| Physical Specifications | |
| LCD | 4 inch, 800*480, visible under sunshine |
| Touch | GFF Captive Touch, Dragontrail Glass |
| Camera | Auto focus 8Mega, with flash LED |
| Keypad | 24 Numeric Keypad Left/Right Scan Key, Left/Right K1,K2 user-defined Key Back, HOME, Switch |
| Receiver | Support |
| Speaker | Min 90db at 10cm-1KHz Voice |
| Mic | Noise Reduction Mic |
| Charging IO | USB type-C, Charging cradle |
| Battery | Removable 3800mAh-4000mAh |
| Dimension | 160×71×17mm |
| Weight | 269g |
| Package | |
| Weight | Gross 750g |
| Package | 255*108*70mm |
| 10 in 1 carton | 370*270*230mm/8.0kg |
| Environmental Specifications | |
| Operation Temperature | -20°C ~ +50°C |

| | |
|---------------------|--------------------------------|
| Storage Temperature | -30°C ~ +70°C |
| Humidity | 10% ~ 90% |
| Drop | 1.5m, concrete, 12 drops |
| Tumble | 600hits, 0.5m, Steel |
| IP | IP65 |
| ESD | ±8kV Contact, ±15kV Air |
| Keypad life cycle | 300K |
| Accessories | |
| Charging Cradle | Support 1 device and 1 battery |
| Hand strap | Black, Nylon |
| Battery | Removable 3800mAh-4000mAh |



Packing Box



Device



Charger

USB Cable



Manuel



Battery



Hand Strip(Optional)



Docking Station (Optional)