

Thermal Transfer and Direct Thermal Barcode Label Printer

(Model: OCBP-002)

Specification:

| | |
|-------------------------|---|
| Printer Model | OCBP-002 |
| Resolution | 203 DPI (8 dot/mm) |
| Printing Method | Direct Thermal / Thermal Transfer |
| CPU | 32 BIT |
| Sensor | Type: Label gap and black mark sensing Detection: label length auto sensing or program command setting |
| Printing Speed | 50.8 mm -101.6 mm / Sec |
| Printing Length | 1727 mm |
| Printing Width | 25 mm ~ 104 mm |
| Media | Paper Roll External Diameter: Maximum Diameter 105 mm Paper Roll Axis: 26 mm Paper Width: 25 mm ~ 110 mm Paper Thickness: 0.06 mm ~ 0.3 mm Media Type: Label gap, Back mark, Continuous |
| Ribbon | Types: Outward Roll External Diameter: 64mm (Max) Length 300M Width: 30 mm ~ 110 mm Core Inner Diameter: 25.4mm (1inch) Material: General Wax Type, Wax/Resin Mixed Type, Resin Type |
| Memory | 2MB Flash Rom, 2MB DRAM |
| Image | Monochrome PCX, BMP (support after the software control: ICOWMFJPGEMF Picture, can control the picture amplification, reduced, rotation, mirror image and highlight |
| Bar Code | Code39, Code93, Code128 (subset A, B, C), UPC A/E (add on 2 & 5), Interleaved 2 of 5, EAN 8/13 (add on 2 & 5), Code bar, China Postal Code, Industrial 2 of 5, Matrix 2 of 5, PDF417 and Data matrix Code, (QR Code Available), Data Matrix |
| Interface | Parallel Port+ USB |
| Transmission Setting | Baud Rate 9600, XON/XOFF, RTS/CTS |
| Control panel | LED*2: Ready, Status Function Key*1: Feed |
| Power | AC 18V, 4000mA |
| Environment | Operating Temperature: 40 Degree F to 104 Degree F (5 Degree C to 40 Degree C) Storage Temperature: -40 Degree F to 122 Degree F (-20 Degree C to 50 Degree C) Operating Humidity: 30% ~ 85%, non-condensing, Free air Storage Humidity: 10% ~ 90%, non-condensing, Free air |
| Physical Dimension | Size: L286mm * H176mm *W233mm Weight: 2.43KG (net) |

Product Details:



**Thermal Transfer and Direct Thermal
Barcode Label Printer**

OCBP-002



Product Picture





Features

Simple but not easy

Two printing methods available:
Thermal Transfer with ribbon and Direct Thermal;





Compatible with plenty of label software;
BMP, PCX images download store;



Support Parallel and USB together;



Suit for thermal paper rolls or
self-adhesive labels;



All-round show



Application Area



Warehouse



Tax Institution



Clothes Store



Airline service



Supermarket



Logistic freight



Drug Store



Bakery Shop

Parameter

| | |
|-----------------|-----------------------------------|
| Printer Model | OCBP-002 |
| Resolution | 203 DPI (8 dot/mm) |
| Printing Method | Direct Thermal / Thermal Transfer |

| | |
|-----------------------------|---|
| LPU | U2 B11 |
| Sensor | Type: Label gap and black mark sensing Detection: label length auto sensing or program command setting |
| Printing Speed | 50.8 mm -101.6 mm / Sec |
| Printing Length | 1727 mm |
| Printing Width | 25 mm ~ 104 mm |
| Media | Paper Roll External Diameter: Maximum Diameter 105 mm Paper Roll Axis: 26 mm Paper Width: 25 mm ~ 110 mm Paper Thickness: 0.06 mm ~ 0.3 mm Media Type: Label gap, Back mark, Continuous |
| Ribbon | Types: Outward Roll External Diameter: 64mm (Max) Length 300M Width: 30 mm ~ 110 mm Core Inner Diameter: 25.4mm (1inch) Material: General Wax Type, Wax/Resin Mixed Type, Resin Type |
| Memory | 2MB Flash Rom, 2MB DRAM |
| Image | Monochrome PCX, BMP (support after the software control: ICOWMFJPGEMF Picture, can control the picture amplification, reduced, rotation, mirror image and highlight |
| Bar Code | Code39, Code93, Code128 (subset A, B, C), UPC A/E (add on 2 & 5), Interleaved 2 of 5, EAN 8/13 (add on 2 & 5), Code bar, China Postal Code, Industrial 2 of 5, Matrix 2 of 5, PDF417 and Data matrix Code, (QR Code Available), Data Matrix |
| Interface | Parallel Port+ USB |
| Transmission Setting | Baud Rate 9600, XON/XOFF, RTS/CTS |
| Control panel | LED*2: Ready, Status Function Key*1: Feed |
| Power | AC 18V, 4000mA |
| Environment | Operating Temperature: 40°F to 104°F (5°C to 40°C) Storage Temperature: -40°F to 122°F (-20°C to 50°C) Operating Humidity: 30% ~ 85%, non-condensing, Free air Storage Humidity: 10% ~ 90%, non-condensing, Free air |
| Physical Dimension | Size: L286mm * H176mm *W233mm Weight: 2.43KG (net) |

Production Line





Capacity

| Verified | Product Name | Production Line Capacity | Actual Units Produced(Previous Year) |
|----------|---------------------------------|--------------------------|--------------------------------------|
| ✓ | Thermal Printer | 40,000 Sets / Month | 250,000 Sets |
| ✓ | Dot Matrix Printer | 15,000 Sets / Month | 10,000 Sets |
| ✓ | Bluetooth Printer | 30,000 Sets / Month | 20,000 Sets |
| ✓ | Barcode Scanner | 40,000 Sets / Month | 20,000 Sets |
| ✓ | POS Machine | 5,000 Sets / Month | 10,000 Sets |
| ✓ | Magnetic Card Reader and Writer | 45,000 Sets / Month | 50,000 Sets |

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

| Verified | Machine Name | Brand & Model No. | Quantity |
|----------|--------------------------|-------------------|----------|
| ✓ | Ageing Tester | No Information | 6 |
| ✓ | Withstand Voltage Tester | CC2670A | 1 |
| ✓ | Oscilloscope | TBS1102 | 1 |
| ✓ | DC Power Supply | PS-305DM | 6 |
| ✓ | Digital Torque Meter | HP100 | 1 |
| ✓ | Calliper | GUANGLU | 2 |
| ✓ | Multi-meter | VC890D | 7 |
| ✓ | Test Computer | No Information | 13 |

Certifications



Packing and Shipment



Payment





Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?



Company Profile

This Assessed Supplier Has Been
Independently Verified

Build Your Growth On Trust



TÜV Rheinland





FORTUNE 500
Precisely Right.



OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Europe, Australia, Asia, and other area.



OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,
Shenzhen 518054, China;

Websites: <http://www.possolution.com.cn> ; <http://www.ocominc.com> ;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



Relevant documents:

Do you want to know more product information? Please Click here. 

[Specification](#)

[Driver for WIN7 Win 8](#)

[Software For Win XP / Win 2000](#)