

Features:

High quality double-walled clamshell design

32-bit RISC CPU

8MB SDRAM,8MB Flash

Head-up sensor

203 dpi resolution

102mm(4'')/s high printing speed

108mm printing width

20-112mm (0.78"-4.4'')adjustable media width

Specifications:

| Parameter | |
|---------------------------|---|
| Resolution | 8 dots/mm(203DPI) |
| Printing method | Direct Thermal |
| Max.print speed | 102 mm (4'')/S |
| Max.print width | 108 mm (4.25'') |
| Max.print length | 2286 mm (90'') |
| Media type | Continuous, gap, black mark, fan-fold and punched hole |
| Media width | 20-112mm (0.78"-4.4'') |
| Media thickness | 0.06~0.16mm((2.36~6.3mil) |
| Label length | 10~2,286mm(0.4''~90'') |
| Label roll capacity | 127 mm (5'') OD (outside wound) |
| Enclosure | Double-walled plastic |
| Physical dimension | 240 mm□W□x 211 mm□H□x 166 mm □D□ |
| Weight | 2.15kg |
| Processor | 32-bit RISC CPU |
| Memory | 8MB Flash Memory, 8MB SDRAM |
| Interface | USB 2.0 / USB+Bluetooth |
| Internal fonts | 8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software. |
| Barcode | 1D bar code□Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST |
| | 2D bar code□PDF-417, Maxicode, DataMatrix, QR code |
| Font and barcode rotation | 0°□90°□180°□270° |
| Environment condition | Operation: 5 ~ 40°C, 25 ~ 85% non-condensing, Storage: -40 ~ 60°C, 10 ~ 90% non-condensing |







