

OCBP-012 4" USB thermal transfer care label printer pvc plastic sticker printer machine (M/N:OCBP-012A/B)

Features

- Direct Thermal / Thermal Transfer Printing;
- 200 MHz 32-Bit RISC Processor;
- 8 MB SDRAM,+8 MB Flash Memory;
- Dual-Motor Gear Driven Design;
- 127 Mm (5") Inches Per Second Print Speed;
- 300 Meter (984') Ribbon Supply On a 25.4 Mm (1") Core;
- 203 dpi or 300dpi resolution for optional;
- Provide free Bartender label edition software;
- Support Gap sensor ,Open lid sensor, Black mark sensor, Ribbon sensor.

Specification

| PRINTER MODEL | OCBP-012A | OCBP-012B |
|-----------------------------|--|---------------------------|
| Resolution | 8 dots/mm(203 DPI) | 12 dots/mm(300 DPI) |
| Printing method | Thermal Transfer & Direct Thermal | |
| Max. print speed | 127 mm (5") / s | 101.6 mm (4") / s |
| Max. print width | 108 mm (4.25") | 104 mm (4.09") |
| Max. print length | 1178mm (70") | 889 mm (35") |
| Media type | Continuous, die-cut, black mark, fan-fold, notched (outside wound) | |
| Media width | 20-112mm (0.78"-4.4") | |
| Media thickness | 0.06 ~ 0.254 mm (2.36 ~ 10 mil) | |
| Label length | 10 ~ 1178 mm (0.39" ~ 70") | 10 ~ 889 mm (0.39" ~ 35") |
| Label roll capacity | 127 mm (5") OD (outside wound) | |
| Ribbon&Ribbon width | 300 m long, max. OD 67 mm, 1" core (ink coated outside) ,40 mm ~ 110 mm (1.6" ~ 4.3") | |
| Enclosure | Double-walled plastic | |
| Physical dimension | 299 mm (D) x 235 mm (W) x 198.3 mm (H) | |
| Weight | 2.55kg | |
| Processor | 32-bit RISC CPU | |
| Memory | 8MB Flash Memory | |
| | 8MB SDRAM | |
| | SD card reader for Flash memory expansion, up to 4 GB | |
| Interface | <ul style="list-style-type: none"> • USB2.0 standard • RS-232 (factory option) • Internal Ethernet, 10/100 Mbps (factory option) • Bluetooth (factory option) • External 802.11 b/g/n wireless (factory option) | |
| Power | External universal switching power supply | |
| | Input: AC 100-240V, 1A, 50-60Hz | |
| | Output: DC 24V, 2.5A, 60W | |
| Operation switch,button,LED | 1 power switch, 1 feed button & 1 LED (3 colors: red, purple & blue) | |
| Sensors | Black mark reflective sensor (position adjustable) | |
| | lid open sensor | |
| | gap sensor | |
| | Ribbon sensor | |

| | |
|---------------------------|---|
| Real Time Clock | Standard |
| Internal fonts | 8 alpha-numeric bitmap fonts Support TTF Font. |
| Bar code | 1D barcode□Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D bar code□PDF-417, Maxicode, DataMatrix, QR code |
| Graphic | BIMAP,BMP,PCX(Max. 256 colors) |
| Font and barcode rotation | 0°□90°□180°□270° |
| Printer language | TSPL |
| Environment condition | Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing |
| Accessories | ①Windows labeling software CD disk□②Quick start guide□③USB cable□④Power cord□⑤External universal switching power supply□⑥Label spindle, fixing tab x 2, 1.5" core adapter x 2□⑦Ribbon spindle x 2□⑧Ribbon paper core□⑨Media |
| Dealer options | Peel-off module, Guillotine cutter (full cut or partial cut) Media thickness 0.06 ~ 0.19mm,500000 cuts;0.20 ~ 0.25mm,200000 cuts |
| User options | External roll mount, media OD. 214 mm (8.4") with 25.4 mm (1") core , External roll mount board, Bluetooth module (serial interface), 802.11 b/g/n wireless module (serial interface), RFIDmodule. |



OCBP-012





OCBP-012





OCBP-012





OCBP-012





OCBP-012





OCBP-012





OCBP-012





OCBP-012



Relevant documents:

[OCOM Label Printer Software and Driver](#)