

## Features:

- 32-bit CPU
- 8MB SDRAM,8MB Flash
- 203 dpi resolution
- 152mm(6'')/s high printing speed
- 108mm printing width
- 25.4-112mm (0.78'-4.56')adjustable media width
- Support TSPL EPL ZPL DPL command

## Specification:

| General                   |  |
|---------------------------|--|
| Model                     | OCBP-014B  |
| Material                  | White plastic housing  |
| Interface                 | USB  |
| Processor                 | 32-bit CPU   |
| Memory                    | 8MB Flash Memory, 8MB SDRAM  |
| Printer Head life         | 30KM   |
| Power supply              | Input AC 100V-240V,50-60Hz,Output DC 24V/2.5A  |
| Sensors                   | Gap sensor,Blackmark sensor,Case-opening sensor  |
| Gap height                | 2mm Min  |
| Blackmark height          | 2mm Min  |
| Font and barcode rotation | 0°,90°,180°,270°   |
| Compatible command        | TSPL EPL ZPL DPL   |
| Printing capability       |  |
| Printing method           | Direct Thermal   |
| Resoluiton                | 203 DPI  |
| Print speed               | 152mm/s Max  |
| Print width               | 108mm Max  |
| Print length              | 1778mm Max   |
| Barcode and character     |  |
| Barcode                   | 1D barcode:<br>Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST<br>2D barcode: PDF-417, Maxicode, DataMatrix, QR code |
| Media                     |  |
| Media type                | Continuous, gap, black mark,fan-fold and punched hole  |
| Media width               | 20-116mm   |
| Media thickness           | 0.06-0.20mm  |
| Label roll capacity       | 101 mm OD (outside wound)  |
| Label length              | 10-1778mm  |
| Physical                  |  |
| Dimension                 | 189.62 mm(W)× 178.5 mm(H)× 219.03 mm(D)  |
| Weight                    | Net:1.78kg Gross: 2.38kg   |
| Package box               | 335*225*235mm  |
| 6 in 1 carton             | 713*350*510mm/15.74kg  |
| Environment               |  |

|                                |   |
|--------------------------------|---|
| Working temperature & humidity | 0 to 45 degrees centigrade, 10%~80% No condensation   |
| Storage temperature & humidity | -20 to 60 degrees centigrade, 10%~90% No condensation |



















**Barcode  
Printer**

