

China high speed One Dimensional CCD Barcode Scanner

(Model:OCBS-C005)

▶ Product Description

Description:

This BarCode Scanner can plug and play, no need to install software.
Efficient decoding rate and ultra-low error rate.
It can accurately and quickly scan a variety bar code in the strong light and dark environment.

Features

- The fast scan speed reach up to 300 times/second.
- 3 mil excellent scanning accuracy.
- Efficient decoding rate and ultra-low error rate. Many kinds of one-dimensional bar code can be identified.
- Support reading bar codes from screen.
- No driver, plug and play.
- High resilient button: Use high rebound button, accurate limit, durable.
- Scanning Mode Setting:Manual trigger and Auto Scanning and Continue Scanning.
- Support multiple data interfaces: USB-HID, USB virtual port, UART, KB, HID-POS, etc.
- Support 16 country language.
- Adopt a highly integrated design, high quality shell, have IP45 protection grade, 5m height fall many times, still can be used normally.
- Application fields:Supermarket, Retail, Warehouse,Logistic,Library, Medical etc.
- Can be customized according to customer demand.

Scanner parameters:

| | | |
|--------------------------------|---|-------|
| Light source type | Optical Imaging; the wave length is 632mm. | |
| Imaging sensor | linear imaging sensor(CCD) | |
| Pixel resolution | 2500 pixels | |
| Barcode precision | ≥ 3mil | |
| Printing Contrast Ratio | ≥ 30% | |
| Barcode type | UPC/EAN/JAN, UPC/EAN with Supplemental, UCC/EAN 128, Code 39, MSI, Code11, Code 39 Full ASCII, Code 39 TriOptic, Code 128, Code 128Full ASCII, EAN-13, EAN-8, UPC-A, UPC-E, ISBN, Code 93, GS1 Databar, Codabar, Code93, Discrete2of5, IATA, RSSvariants, Codabar, Chinese2of5, International general dimensional barcodes, e.g. Inteleaved2/5, Interleaved2of5,China postal service code and so on | |
| Scanning speed | 300times/s | |
| Scanning angle | Clockwise/anticlockwise | ±55° |
| | Up and down | ±25° |
| | Left and right | ±75° |
| External dimensions(L x W x H) | 165×65×97 mm | |
| Weight | 190g | |
| prompting Mode | Buzzer and LED indicator | |
| Maximum power consumption | 650mw | |
| Working voltage | DC5V | |
| Electric current | Maximum current | 130ma |
| | Working current | 86ma |
| | Standby current | 42ma |

| | |
|---------------------|--|
| Accessories | |
| Cable | RS232/USB data cable(1.8m) |
| Manual | 1 |
| Environment | |
| Storage temperature | -40°C ~ 60°C |
| Work temperature | 0°C ~ 50°C |
| Relative humidity | 0 ~ 95% |
| Anti-knock | working fine after fall from 5m height |

▶ Picture Show



OCBS-C005





OCBS-C005





OCBS-C005





OCBS-C005





OCBS-C005





OCBS-C005



▶ Application scenario

Logistics



Warehouse management



Supermarket



Clothing label



Jewelry label



Restaurant



▶ Company



▶ Certificates



▶ Payment



▶ Contact us



Monica Fu



OCOM Technologies Limited

Add: 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Tel: 0086.755.8605.3207 ext 801

Fax: 0086.755.8605.3207 ext 868

Web: www.ocominc.com

E-mail: sales01@ocominc.com, sales01@ocomtech.com.cn

Skype: ocomsales01; **MSN:** ocomsales01@hotmail.com

Ali TM: cn1001868228; **QQ:** 1483705401

Mobile/Wechat/Whatsapp: 0086.189 4871 3992



Reliable One-Stop Supplier for POS and Auto-ID Related Products