

Supermarket 360 degree desktop usb Windows Android rugged 1d  
2d omnidirectional barcode scanner

(M/N:OCBS-T215)

Features:



Large reading window;

Quickly identify the screen 1D/2D code;

Hidden anti-pull data cable socket.

# Specification

<b>General</b>	
Model	OCBS-T215
Interface	USB
Operating Voltage	5V
Starting Current	420mA
Work Current	400mA
Standby Current	270mA
<b>Performance</b>	
Sensor	Overall exposure 640*480 CMOS sensor
Light source	Red LED
Field view	57.2° (H), 44.2°(V)
Motion tolerance	> 0.3m/s
Scan Angle	Pitch ±70°@ 0°Roll and 0° Skew Roll 360°@ 0°Pitch and 0° Skew Skew ±70°@ 0°Roll and 0° Pitch
Symbol Contrast	20% minimum reflective difference
Ambient Light Immunity	0-100,000 Lux
Typical Depth of Field	Code39(5mil):20mm-80mm, EAN13(13mil):10mm-160mm QR(15mil):10mm-140mm Data Matrix (15mil):10mm-100mm PDF417 (10mil):10mm-120mm
Decoding ability	(Codabar),(Code 39),(Code 32),(Industrial 2 of 5),(Interleaved 2 of 5),(Standard 2 of 5),(Matrix 2 of 5),(Code 93),(Code 11),(Code 128),(UPC-A),(UPC-E),(EAN/JAN-8),(EAN/JAN-13),(GS1 DataBar(RSS14) (PDF417),(QR Code),(Micro QR),(Data Matrix),(Aztec),(Hanxi code)
<b>Physical</b>	
Weight	Gross:640g
Package	230*170*95mm
<b>Environment</b>	
Working temperature& humidity	0 to 45 degrees centigrade , 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation

















Model: OCBS-T215

Interface: USB



OCBST2152214100001

Made in China





1. Introduction	1
2. Safety Precautions	2
3. Operation	3
4. Troubleshooting	4
5. Appendix	5

**Special Precautions Manual**

1. The device and also its charging socket  
operation under the mark of the device. When charging  
applied or placed under use for more or more long, and  
the time limit.

2. The device shall not be exposed to a fire, with which  
and a small amount of gasoline can be added to the device,  
and then exposed only with known water.

3. Special Precautions: This instruction has been strictly and  
carefully checked and confirmed, but it will have not  
verified the instructions and errors or spelling and  
handwritten work, minimums and errors will be corrected in  
the next version of the instruction without notice, the  
copyright of this instruction is owned by the company, and  
no other work or reproduction may modify it.

**THE DEVICE IS NOT TO BE USED IN  
THE FOLLOWING SITUATIONS**



Information: This device is not to be used in the following situations:  
- In the presence of flammable or explosive gases, vapors or dusts.  
- In the presence of high voltage or high frequency electromagnetic fields.  
- In the presence of strong magnetic fields.  
- In the presence of strong electric fields.  
- In the presence of strong radio frequency fields.  
- In the presence of strong static electric fields.  
- In the presence of strong static magnetic fields.  
- In the presence of strong static electric fields.  
- In the presence of strong static magnetic fields.  
- In the presence of strong static electric fields.  
- In the presence of strong static magnetic fields.





**2D Barcode Scanner**  
Model: OCBS-T215      Color: Black  
Interface: USB      CE FC  
Power Input: 5V1A  
  
OCBS T2152214100001  
Made in China