

# Cheap 200mm/s handheld 1D laser wireless barcode scanner with receiver

(Model No.: OCBS-W013)

## Feature:

200MM/S Scan Speed

10-60cm long depth of field

70 m long Distance 2.4G Wireless transmission

Compatible with multiple language layouts

1.5m free fall on concrete surface

1500mAh lithium-ion battery

## Specification:

Physical Parameters	
Material	ABS+PVC+PC
Size	L*W*H: 162mm * 68mm * 93mm
Weight	169g±5g(without cord)
Power Supply	5V ±5% ,Built-in 3.7v 1500mAh lithium-ion battery
Operating current	50MA(operating mode); 30MA(standby mode)100MA(maximum peak)
Color	white,black
Button Lifespan	>100000
Performance Parameters	
Interface	USB cable;Wireless 2.4G transmission
System Supported	Linux,Android,Windows XP,7,8,10,MAC
Language Supported	English(Customizable language)
Light source	Visible laser diode, wavelength 650nm
Processor	32-bit MCU
Memory	64K(About 3500 14bit 1D barcodes)(the memory capacity can be customized)
Scanning speed	200 scans/sec
Resolution	4mil
Transmission Distance	70m
Bit Error Rate	1/5000000
Reading Mode	laser
Trigger Mode	Manual ;Continuous scanning
Prompt Mode	Buzzer, Indicator Light(LED)

Print Contrast	35%
Charging time	6-7 hours
Working time	about 24 hours
Decoding Capability	Code25-Interleaved    Code25-Standard    Code25-Matri Code39-Regular        Code39-FullASCII    Code32 Code93-Regular        Code93-FullASCII    Code128
Scanning Distance	10mm-600mm
Scanning Angel	Roll35°;Pitch65°;Yew65°
Scanning Depth	Code39 5mil:3cm - 8cm Code39 10mil:4cm - 45cm
Environment Parameters	
IP Grade	IP52
Operating Temp.	0 to 50°C / 32 to 122°F
Storage Temp.	0 to 50°C / 32 to 122°F
Operating Humidity	20% to 85%(No Condensation)
Storage Humidity	20% to 85%(No Condensation)
ESD Protection	15KV air discharge
Shock Resistance	1.5m free fall on concrete surface



OCBS-W013





OCBS-W013





OCBS-W013





OCBS-W013





OCBS-W013





OCBS-W013

