

Features:

- 200MM/S Scan Speed
- 10-60cm long depth of field
- 70 m long Distance 2.4G Wireless transmission
- Compatible with multiple language layouts
- 1.5m free fall on concrete surface
- 1500mAh lithium-ion battery

Specification:

| | |
|-------------------------------|---|
| General Information | |
| Model | OCBS-W013 |
| Color | white,black |
| Material | ABS+PVC+PC |
| IP Grade | IP52 |
| Processor | 32-bit MCU |
| Button Life | >100000 |
| Interface | USB cable;Wireless 2.4G transmission |
| Language Supported | English(Customizable language) |
| Power Supply | 5V ±5% ,Built-in 3.7v 1500mAh lithium-ion battery |
| Operating current | 50MA(operating mode); 30MA(standby mode)100MA(maximum peak) |
| Prompt Mode | Buzzer, Indicator Light(LED) |
| Trigger Mode | Manual ;Continuous scanning |
| Memory | 64K(About 3500 14bit 1D barcodes)(the memory capacity can be customized) |
| Working time | about 24 hours |
| Charging time | 6-7 hours |
| ESD Protection | 15KV air discharge |
| Shock Resistance | 1.5m free fall on concrete surface |
| System Supported | Linux,Android,Windows XP,7,8,10,MAC |
| Scanning Performance | |
| Light source | Visible laser diode, wave length 650nm |
| Scanning speed | 200 scans/sec |
| Scanning Distance | 10mm-600mm |
| Print Contrast | 35% |
| Resolution | 4mil |
| Transmission Distance | 70m |
| Reading Mode | laser |
| Scanning Angel | Roll35°;Pitch65°;Yew65° |
| Scanning Depth | Code39 5mil:3cm - 8cm Code39 10mil:4cm - 45cm |
| Bit Error Rate | 1/5000000 |
| Decoding ability | Code25-Interleaved Code25-Standard Code25-Matrix Code39-Regular Code39-FullASCII Code32 Code93-Regular Code93-FullASCII Code128 |
| Physical Dimensions | |
| Weight | Gross:300g |
| Package | 183*118*85mm |
| 20 in 1 carton | 460*400*270mm/7.05kg |
| Environment | |
| Working temperature& humidity | 0 to 45 degrees centigrade, 10%~80% No condensation |
| Storage temperature& humidity | -20 to 60 degrees centigrade , 10%~90% No condensation |









