

Features:

200MM/S Scan Speed
 10-60cm long depth of field
 70 m long Distance 2.4G Wireless transmission
 Compatible with multiple language layouts
 1.5m free fall on concrete surface
 1500mAh lithium-ion battery

Specification:

Model	OCBS-W013		
Color	white,black		
Material	ABS+PVC+PC		
IP Grade	IP52		
Processor	32-bit MCU		
Button Life	>100000		
Interface	USB cable;Wireless 2.4G transmission		
Language Supported	English(Customizable language)		
Power Supply	5V ±5% ,Built-in 3.7v 1500mAh lithium-ion battery		
Operating current	50MA(operating mode); 30MA(standby mode)100MA(maximum peak)		
Prompt Mode	Buzzer, Indicator Light(LED)		
Trigger Mode	Manual ;Continuous scanning		
Memory	64K(About 3500 14bit 1D barcodes)(the memory capacity can be customized)		
Working time	about 24 hours		
Charging time	6-7 hours		
ESD Protection	15KV air discharge		
Shock Resistance	1.5m free fall on concrete surface		
System Supported	Linux,Android,Windows XP,7,8,10,MAC		
Light source	Visible laser diode, wave length 650nm		
Scanning speed	200 scans/sec		
Scanning Distance	10mm-600mm		
Print Contrast	35%		
Resolution	4mil		
Transmission Distance	70m		
Reading Mode	laser		
Scanning Angel	Roll35°;Pitch65°;Yew65°		
Scanning Depth	Code39 5mil:3cm - 8cm Code39 10mil:4cm - 45cm		
Bit Error Rate	1/5000000		
Decoding ability	Code25-Interleaved	Code25-Standard	Code25-Matrix
	Code39-Regular	Code39-FullASCII	Code32
	Code93-Regular	Code93-FullASCII	Code128
Weight	Gross:300g		
Package	183*118*85mm		
20 in 1 carton	460*400*270mm/7.05kg		
Environment			
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation		
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation		









