

# HandHeld 2D Wireless Barcode Scanner

(M/N:OCBS-W239)

## Features:

1. 2.4G or 2.4G +Bluetooth for option
2. 300,000 pixel and global exposure high precision scanning engine
3. Low power design can scan 20,000 times
4. Scanning high density barcode has high performance
5. Superior performance for Small two-dimensional codes
6. Cradle is for charging and receiving

## Specification

|                               |  |
|-------------------------------|--|
| Model                         | OCBS-W239  |
| Wireless function             | 2.4G or 2.4G+Bluetooth for option  |
| Battery                       | 3.7V/2500mAh (20000 times scan and transmission)   |
| Prompting Mode                | LED / buzzer   |
| Working Voltage               | +4.2V±10% VDC  |
| Working current               | 226mA  |
| Starting Current              | 204mA  |
| Standby current               | 96mA   |
| Shock Specifications          | Designed to withstand 1.5m drops   |
| Illumination                  | White LED  |
| Aiming                        | Red LED  |
| Image sensor                  | CMOS   |
| Image resolution              | 640*480  |
| Print contrast                | ≥ 20% minimum reflective difference  |
| scan angle                    | Roll/Pitch/Yaw:65°Yaw,65°Pitch,360°Roll  |
| Decoding ability              | 1D :Codabar,Code 39,Code 32 Pharmaceutical (PARAF),Interleaved 2 of 5,NEC 2 of 5,Code 93,Straight 2 of 5 Industrial,Straight 2 of 5 IATA,Matrix 2 of 5,Code 11,Code 128,GS1-128,UPC-A,UPC-E,EAN/JAN-8,EAN/JAN-13,MSI,GS1 DataBar Omnidirectional,GS1 DataBar Limited,GS1 DataBar Expanded,China Post(Hong Kong 2 of 5),Korea Post 2D:Codeblock A,Codeblock F,PDF417,Micro PDF417,GS1 Composite Codes,QR Code,Data Matrix,MaxiCode,Aztec,HANXIN |
| Depth of scan field           | Code 39 (4 mil) : 6 - 15 cm<br>, Code39(5 mil):4-20cm,Code39(13mil):6-35cm<br>QR(15mil):4-20cm, QR(20mil):3-25cm, QR(30mil):3-35cm<br>UPC-A(13mil):4-35cm,ENA-13(5mil): 6-15cm,ENA-13(5mil): 3-35cm  |
| Weight                        | Gross:290g   |
| Package                       | 122*165*105mm/493g   |
| 30 in 1 carton                | 525*430*360mm/16.5kg   |
| <b>Environment</b>            |  |
| Working temperature& humidity | 0 to 45 degrees centigrade, 10%~80% No condensation  |
| Storage temperature& humidity | -20 to 60 degrees centigrade , 10%~90% No condensation   |







































