

# 80MM Thermal Printer with Auto Cutter

□Model NO.: OCPP-80T□

## Features:

- u. Supports multi 1D barcode and QR code printing.
- v. Support printer status monitoring function
- w. 100M Ethernet port, ultra high speed data transmission.
- x. 256KB NV Logo storage and 256kb big buffer memory.
- y. Compatible with OPOS/JPOS driver.
- z. 100KM long life printer head

## Technical parameters□

Print Method	Direct Thermal
Command	ESC/POS
Resolution	576dots/line or 512dots/line
Printing Width	Max=72mm
Paper Type	Thermal Receipt Paper
Interface	USB/UL/U+BT/ U+WIFI
Print Speed	200 mm/s □U□ 260 mm/s (UL/U+BT/U+WIFI)
Paper Width	80mm
Paper Thickness	0.06~0.08mm
Roll Dia	Max. Ø 83 mm
Paper Cut	Manual tear and Auto-cutter
Input buffer	256kbytes
NV Flash	256kbytes
Font Size	font A:12*24(standard), font B:9*17
Chinese	GB18030,BIG5 24x24dots
Japanese/Korea	Support
User-defined language	PC347(Standard Europe),Katakana,PC850(Multilingual),PC860(Portuguese),PC863(Canadian-French),PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2),PC858,IranII,Latvian,Arabic,PT151(1251) ect.
1D	UPC-A/UPC-E/JAN13□EAN13□/JAN8□EAN8□/CODE39/ITF/CODABAR/CODE93/CODE128
2D	QR code ( <b>Single USB or UR solution no QR code function</b> )
Printing head life	100 KM
Cutter life	1million
Sensors	Paper out, cover open, cutter jam,paper jam and black mark detection(Optional)
Input	AC 100V-240V 50/60HZ
Output	DC 24V/2.5A
Working Condition	0°C~45°C, 10%~80%RH
Storage Condition	-10°C-60°C,10%~90%RH
Accessories	Data cable,power code,paper roller>manual, (standard)
Dimensions	180(D)x142(W)x136(H)mm
Net weight	1.14kg
Gross weight	1.8kg
8 in 1 carton	48*45*36cm/13.4kg
Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS
SDK	Android, IOS
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation

Storage  
temperature&  
humidity

-20 to 60 degrees centigrade , 10%~90% No condensation