

# OCPD-LCD500 5" USB TFT LCD pos customer display with OPOS driver

(M/N:OCPD-LCD500)

## Features:

Support OPOS driver;

Compatible with 15 kinds command,like ESC/POS,CD5220 and so on;

Compatible with 20 countries Languages,other languages can be customized;

Provide custom setup software all customizations can be done by the end user;

Support setting booting image;

Three display areas can setting background color and character color;

Top display area can setting logo and fixed characters;

The middle display area can be switched to 2\*20 characters or 4\*20 characters display;

The bottom display area supports custom scrolling play characters.

## Data sheet:

General	Display Method	TFT - LCD Display□5 inch COLOR PANEL□
	Number of characters	40 character(20columns×2line )/ 80 character(20columns×4 line)
	Brightness	□350cd/m2
	Resolution	480*272 or 800*480
	Character font	24*48/40*80 dot matrix
	Character type	95 Alphanumeric□32 international characters
	Character size	8□H□×5.25□W□mm
	Dot size□X×Y□	0.23×0.23mm
	Panel Dimension	113.5□L□mm×65.5□W□×40□H□
	Pole Dimension	Per support length□163□L□×27.65□DIA□mm/ 80□L□×27.65□DIA□mm
	Base Dimension	126□L□×89□W□×13.5□H□mm
	Viewing Angle	Max.135°
	Horizontal Rotation	Max.355°
	Weight	490 grams/506grams
Commands Mode	15 kinds, E.g LD220, ESC/POS, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL etc	
Language Support	CP437, Katakana, CP850, CP860, CP863,CP865, WCP1252, CP857, WCP1250, WCP1253,WCP1255, WCP1251, CP866, CP852, CP737, CP858, CP864,WCP1257, WCP1258□Tai□CP874□	
Interface	RS-232□serial□/USB	

Connection	Baud	Direct connection 9600/19200/38400/57600/115200 bps
Reliability	MTBF	30000 hours
Power	Consumption	5-24 VDC
Safety	EMC standards Safety standards	FCC CE ROHS





# OCPD-LCD500





# OCPD-LCD500





# OCPD-LCD500





# OCPD-LCD500

