

58mm Thermal Receipt Printer

(OCP-58E)

Parameters:

| Items | Parameters | |
|--------------------------|------------------------|--|
| Print parameters | Printing Method | Thermal Line |
| | Printing Width | 48MM |
| | Resolution | 384dots/Line(8dots/mm,203dpi) |
| | Printing Speed | 90mm/Second |
| | Interface Type | USB,USB+Bluetooth |
| | Line Spacing | 3.75 mm(Can adjust line spacing by command) |
| | Line No. | Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines |
| | Character | Standard GB18030 simplified / traditional Chinese Fonts |
| | Character Size | ANKcharacter,Font A:1.5×3.0mm(12×24dots) Font B:1.1×2.1mm(9×17dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots) |
| Bar code Character | Extended character set | PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/ EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251 /PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/ (WPC1257)/(PC864)/(Vietnam)/(Thai) |
| | Bar code | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 |
| Graphics printing | Graphics printing | Supports bitmap download and print |
| Paper | Type | Thermal Roll |
| | Width | 57.5±0.5mm |
| | Diameter | ≤60mm |
| | Feed Method | Easy feed(Clameshell feed) |
| Print commands | Commands | ESC/POS |
| Power | Power Adaptor | Input:AC 100V-240V,50-60Hz Output:DC 12V/2A |
| | Casher Drawer output | DC 12V/1A |
| Buffer | Input Buffer | 4K |
| | NV Flash | 40K |
| physical characteristics | Weight | 590g |
| | Dimension | 185*130*112(MM) |
| Environment | Working | Temp:5 ~ 45°C, Humidity:10 ~ 80% |
| | Storage | Temp:-10 ~ 50°C ,Humidity:10 ~ 90%(No dew) |
| Reliability parameter | Print Head Life | 50KM(print density≤12.5) |



OCPP-58E





OCPP-58E





OCPP-58E





OCPP-58E



Model: OCPP-58E
Print Speed: 100mm/s
Print Resolution: 203dpi
Print Density: 1200x1200
Current Codepage: 94
Support Character:
Simplified Chinese (GB18030)
Alphanumeric
CODE BAR:
1-UPC-A
2-UPC-E





OCPP-58E

