OCPP-58E OCOM 58mm gr code restaurant bill receipt pos thermal printer

(OCPP-58E)

ProductIntroduction:

OCPP-58E is a well-designed economic printerfor common thermal bill printing ,this mold is with solid material, Exquisiteworkmanship. Transparent cover design, simple and fashion, easy for users toknow the paper rolls' Using status, OCPP-58E adopt built-in power supply, notonly can save space, but also easy for users to configure and use the printers. It's a very good choice for economical printing.

ProductFeatures

Simple and fashion, With solid material, exquisite workmanship.

Easy paper install structure, simple and convenient to operate

Built-in power supply design, to save space and more convenient to configure;

Transparent cover design, the user can know the paper roll's using status anytime;

Support GB18030 big font, easy to print uncommon characters

Support multi language print, suitable for users all over the world;

Support download and print LOGO & graphics;

Support Windows, Linux, Android and IOS system printing

ApplicationArea

Shoppingmalls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters

Items		Parameters
Print parameters	Printing Method	Thermal Line
	Printing Width	48MM
	Resolution	384dots/Line[8dots/mm[203dpi]
	Printing Speed	90mm/Second
	Interface Type	USB[]USB+Bluetooth
	Line Spacing	3.75 mm Can adjust line spacing by command
	Line No.	Font A:32 character /Line
		Font B:42 character/Line
		Simple,traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANKcharacter[Font A[]1.5×3.0mm[]12×24dots[]
		Font B[]1.1×2.1mm[]9×17dots[] Simplified/Traditional Chinese[]3.0×3.0mm(24×24 dots[]
Bar code	Extended	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran
Character	character set	/WPC1252/PC866/PC852/PC858/Iranll/Latvian/Arabic/PT151,1251/PC737/WPC/1257/
		Thai
		Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/
		CODABAR/CODE93/CODE128
Graphics	Graphics printing	Supports bitmap download and print
printing		
Paper	Туре	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed Method	Easy feed(Clameshell feed)
Print	Commands	ESC/POS
commands		

Power	Power Adaptor	Input∏AC 100V-240V,50-60Hz Output∏DC 12V/2A
	Casher Drawer	DC 12V/1A
	output	
Buffer	Input Buffer	4K
	NV Flash	40K
physical	Weight	590g
characteristics	Dimension	185*130*112(MM)
Environment	Working	Temp[5 ~ 45°C[] Humidity[10 ~ 80%
	Storage	Temp[]-10 ~ 50°C []Humidity[]10 ~ 90%[]No dew[]
Reliability	Print Head Life	50KM[print density≤12.5[]
parameter		