

# OCPP-58X Cheap Model 58MM Bill Print POS Direct Thermal Photo Printer

(OCPP-58X)

## Product Description

### Product Introduction:

OCPP-58X is a well-designed economic printer for common thermal bill printing , It is adopt built-in power supply,not only can save space,but also easy for users to configure and use the printers.It's a very good choice for economical printing.

### Product Features

- Simple and fashion,With solid material,exquisite workmanship.
- Easy paper install structure,simple and convenient to operate
- Built-in power supply design, to save space and more convenient to configure;
- Support multi language print, suitable for users all over the world;
- Support download and print LOGO&graphics ;

### Application Area

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

### Parameters

Items	Parameters	
Print parameters	Printing Method	Thermal Line
	Printing Width	88MM
	Resolution	84dots/Line 8dots/mm 203dpi
	Printing Speed	80mm/Second
	Interface Type	USB  Parallel
	Line Spacing	2.75 mm Can adjust line spacing by command
	Line No.	Font A:32 character/Line Font B:42 character/Line Simple(traditional) Chinese-16 lines
Character	Character	Standard GB2312 simplified Chinese Fonts
	Character Size	ANKcharacter Font A 1.5×3.0mm 12×24dots  Font B 1.1×2.1mm 9×17dots  Simplified/Traditional Chinese 3.0×3.0mm 24×24 dots
Bar code Character set	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/iran Latvian/Arabic/PT151,1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/Latvian PC1001 PT151,1251 (WPC1257) (PC864) (Vietnam) (Thai)
	Bar code	UPC-A UPC-E JAN13 EAN13 JAN8 EAN8 CODE39 ITF  CODABAR CODE93 CODE128
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	860mm
	Feed Method	Easy feed(Clamshell feed)
Print commands	Commands	ESC POS
Power	Power Adaptor	Input AC 100V-240V,50-60Hz Output DC 12V/2.6A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	32 KB
	WV Flash	64 KB

## Picture Show



# OCP-58X



Self test  
Version : 1.9f  
Speed : 90mm/s  
Interface : Parallel  
Default code page: Page0  
Print Density : Light  
Chinese character: Yes  
Image NV Download: Yes  
Modify date : 2013/12/30  
Resident Character:  
Alphabet





OCPP-58X





OCPP-58X





OCP-58X





OCPP-58X





OCPP-58X



## ▶ Company



## ▶ Certificates



## ▶ Payment



## ▶ Contact us



Anna Zhuang



## OCOM Technologies Limited

---

**Add:** 4F(3A01), Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518054, China

**Tel:** 0086.755.8605.3207 ext 805

**Fax:** 0086.755.8605.3207 ext 868

**Web:** [www.ocominc.com](http://www.ocominc.com); **QQ:** 2065804330

**E-mail:** [sales05@ocominc.com](mailto:sales05@ocominc.com), [sales05@ocomtech.com.cn](mailto:sales05@ocomtech.com.cn)

**Skype:** ocomsales05; **MSN:** ocomsales05@hotmail.com

**Mobile/Wechat/Whatsapp:** 0086.133 9282 8710



Reliable One-Stop Supplier for POS and Auto-ID Related Products