

# Thermal Receipt Printer Comply 58/80 Paper Rolls

(Model No.: OCPP-80582)

## Features:

Support 58/80MM width thermal paper roll

Desktop or wall-mounted type for option.

Supports multi 1D bar codes and 2D bar codes printing.

100M Ethernet port, ultra high speed data transmission.

Supports 256KB NV Logo storage and 2M big buffer memory.

Supports black mark detection and order reminding function,

Compatible with OPOS driver.

Supports printing status monitor and anti-losing order function.

Standard hidden cable slot can make the table more tidy

## Technical parameters

Printing method:	Direct thermal
Printing speed:	200mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line512 Dots/line
Line's pacing :	3.75mmAdjustable by commands
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+Lan
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0~45) humidity(10~80%)Non- condense
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10~60°C); Humidity(10~90%)
Character size:	ANKFontA:1.5*3.0mm/ FontB1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA/EAN13/JAN8/EAN8/CODE39/ITF/ CODE93/CODE128/QRCode/PDF417 (options)
Characters:	PC347Standard EuropeKatakanaPC850MultilingualPC860PortuguesePC863Canadian-FrenchPC865NordicWest EuropeGreekHebrewEast EuropeIranWPC1252PC866Cyrillic#2PC852Latin2PC858IranII/LatvianArabicPT1511251
Physical characteristics	Weight: 1.45Kg; Appearance size: 190×145×143mm (length * width * height)



OCPP-80582





OCPP-80582



Relevant documents:

[OCPP-80582\\_SPEC](#)