

(OCPP-80K) Thermal Receipt Printer With Auto Cutter Mobile 58mm 80mm Wifi Bluetooth

(M/N:OCPP-80K)



Features:

It can be used as top paper coming printer and front paper coming printer

It's built-in power adaptor, which avoids messy cords everywhere, saving much space

Support 8 kinds abundant interface combination

Supports multi 1D barcode and QR code printing

Support printer status monitoring function

Support printing queuing ticket function

100M Ethernet port, ultra high speed data transmission

256KB NV Logo storage and 256kb big buffer memory

48 or 80mm adjustable paper separator for option

100KM long life printer head

Specifications:

| | |
|-------------------------------|---|
| General | |
| Model | DCP-80K |
| Name | 80mm desktop thermal printer with auto cutter |
| Color | Black |
| Interface | USB/USB+LAN/USB+BT/USB+WIFI/URL+WIFI/URL+BT/USB+RS232 |
| Power supply | Input:AC 100V-240V/50-60Hz,Output:DC 24V/2.5A |
| Cash drawer | DC 24V/1A |
| Graphics printing | Supports bitmap download and print (each bitmap size Max 20K) |
| Printer head lifespan | 100KM |
| Cutter | Auto cutter |
| Sensors | Paper out, cover open, cutter jam,paper jam and black mark detection(Optional) |
| Buffer | Print buffer:256K/UV Flash 256K |
| Accessories | Data cable,power adaptor,power cord,paper roller,CD,manual, Paper separator(optional) |
| OS supporting | Compatible with IOS/ Android/ Windows |
| Safety standards | CE ,FCC,Rohs etc |
| Printing capability | |
| Printing method | Direct thermal line |
| Resolution | 378 Dots/Line or 512 Dots/Line(8dots/mm, 203dpi) |
| Printing speed | 200mm/s (USB) 260mm/s (URL+BT/ U+ WIFI) 200mm/s (URL/ URL+BT/ URL+WIFI) |
| Print width | 72mm |
| Graphics printing | Supports bitmap download and print |
| Printing Command | Compatible with ESC/POS |
| Barcode and character | |
| Barcode | 1D barcode: JPC-A/JPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/COUPON/CODE93/CODE128 2D barcode:QR_CODE/Single USB or UR solution no QR code function |
| Character | Standard GB18030 simplified / traditional Chinese Fonts |
| Character size | 384dots/line, AWK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm FontB:9*17dots, 1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm |
| Japanese/Korea | Optional |
| User-defined language | PC437/Katakana(PC850/PC860/PC863/PC865/WesteEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Iran/Latvian/Arabic/PT151.1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/Latvian/PC1001/PT151.1251/WPC1257/PC864/Vietnam/IThai) |
| Media | |
| Paper type | Thermal roll paper |
| Paper width | 48mm/52mm/56mm/64mm/68mm/76mm/80mm |
| Paper Thickness | 0.08-0.09mm |
| Paper roll diameter | 83mm Max |
| Paper separator | Optional |
| Physical | |
| Dimension | 198*145*135mm |
| Weight | 1.65kg |
| Package box | 300*190*180 mm |
| 12 in 1 carton | 615*370*335mm/21.5kg |
| Environment | |
| Working temperature& humidity | 0 to 45 degrees centigrade, 10%–80% No condensation |
| Storage temperature& humidity | -20 to 60 degrees centigrade, 10%–90% No condensation |

Product details:

