

80MM Thermal Printer with Auto Cutter

□Model NO.: OCPP-80T□

Features:

1. Support 8 kinds abundant interface combination
2. Supports multi 1D barcode and QR code printing.
3. Support printer status monitoring function
4. 100M Ethernet port, ultra high speed data transmission.
5. 256KB NV Logo storage and 256kb big buffer memory.
6. Compatible with OPOS/JPOS driver.
7. 100KM long life printer head

Technical parameters□

Print Method	Direct Thermal
Command	ESC/POS
Resolution	576dots/line or 512dots/line
Printing Width	Max=72mm
Paper Type	Thermal Receipt Paper
Interface	USB/UL/U+BT/ U+WIFI
Print Speed	200 mm/s □U□ 260 mm/s (UL)
Paper Width	80mm
Paper Thickness	0.06~0.08mm
Roll Dia	Max. Ø 83 mm
Paper Cut	Manual tear and Auto-cutter
Input buffer	256kbytes
NV Flash	256kbytes
Font Size	font A:12*24(standard), font B:9*17
Chinese	GB18030,BIG5 24x24dots
Japanese/Korea	Support
User-defined language	PC347(Standard Europe),Katakana,PC850(Multilingual),PC860(Portuguese),PC863(Canadian-French),PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2),PC858,IranII,Latvian,Arabic,PT151(1251) ect.
1D	UPC-A/UPC-E/JAN13□/EAN13□/JAN8□/EAN8□/CODE39/ITF/CODABAR/CODE93/CODE128
2D	QR code (Single USB or UR solution no QR code function)
Printing head life	100 KM
Cutter life	1million
Paper separator	Optional
Sensors	Paper out, cover open, cutter jam,paper jam and black mark detection(Optional)
Input	AC 100V-240V 50/60HZ
Output	DC 24V/2.5A
Working Condition	0°C~45°C, 10%~80%RH
Storage Condition	-10°C-60°C,10%~90%RH
Accessories	Data cable,power adaptor,power code,paper roller,CD>manual, (standard) Paper separator(option)
Dimensions	180(D)x142(W)x136(H)mm
Net weight	1.14kg
Gross weight	1.8kg
Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS
SDK	Android, IOS









Selftest

Firmware version : 1.3206a
Print Speed : 280mm/s
Command mode : EPSON (ESC/POS)
Firmware mode : 2000/02/12
Cutter enable : No
Feeder enable : No
Black mark mode : 5 (Max=6)
Density Level :
Character per line : 48/84
Default ASCII FONT : FONT1
Default code page : Page0
Default W/Load : Yes
Stackmark SEAS L : 8, 12
Align Load : 000
Align Load : 000
Align Load : 000
Align Load : 000









Thermal Printer



Together we quest for the best



ACOM Thermal Receipt Printer
Model: DCFP-801 Cutter: YES
Interface: USB/LAN Paper Width: 80mm
Power Input: 24V/0.5A Print Speed: 360mm/sec
Cash Drawer: 34411A
OCPP9072232400007
CE FCC Made in China

Thermal Printer



Together we quest for the best

