

Features:

Mini size suitable for portable application

Windows, Java, Linux, Android (or Android +IOS) operation system supported

Bluetooth, USB and RS232 communication supported

SDK for Android available

One printer can connect up to 8 smart devices (7 Android, one Apple device) visa bluetooth

Low power consumption and large capacity Lithium battery (1500mAh), 4~5 days standby

Powered by rechargeable battery,power adapter,or car charger(specified models)

Higher print speed 90mm/sec

50km thermal printer head life

Multiple languages supported

ESC/POS command set compatible

Specification:

General	
Model	OCP-06
Name	58mm mini portable bluetooth thermal printer
Color	Black
Interface	USB, RS-232,Bluetooth (optional)
Battery	7.4V DC/ 1500mAh rechargeable li-ion battery
Power adaptor	DC 9v/1.5-2A
Standby time	4-5days after fully charged
Buffer	Input buffer:Up to 20K,Flash:256K
Other function	Paper detection, Power detection, Manual shut down, 1D&QR Code Print
Device name	Can be customized
TPH life	50KM
Password	Enter default pairing code "1234", it can be customized or change by customers, At max 6 digitals
Accessories	Data cable,power adaptor,power cord,paper roller,CD,manual
Power plug dimension	3.5*1.1mm
OS supporting	Windows &Android & IOS Systems
Safety standards	CE ,FCC,Rohs etc
Printing capability	
Printing method	Direct thermal line
Resoluiton	203DPI (8dot/mm)
Printing speed	70mm/sec (Max 90mm/sec)
Print width	48mm
Continuous printing	120 pieces Thermal Roll for fully charged battery
Characters per Line	Font A:32 character /Line Simple,traditional Chinese:16 character /Line
Printing Command	Compatible with ESC/POS
Barcode and character	
Character size	FontA: 12*24dots, 1.5(W)*3.0(H) Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Character set	Alphanumeric/ Chinese Kanji
Media	
Paper type	Thermal roll paper
Paper width	57.5±0.5mm
Paper feeding method	Easy paper loading

Paper roll diameter	40mm Max
Paper thickness	0.06-0.08mm
Physical	
Dimension	105*75*45mm
Weight	Net:360g Gross:440g
Package box	190*120*70 mm
40 in 1 carton	380*475*340mm/18.36kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation











