

# 58mm Mini Portable Bluetooth Thermal Printer

(M/N:OCPM-M06)

## Features:

1. Mini size suitable for portable application
2. Windows, Java, Linux, Android (or Android +IOS ) operation system supported
3. Bluetooth, USB and RS232 communication supported
4. SDK for Android available
5. One printer can connect up to 8 smart devices (7 Android, one Apple device) via bluetooth
6. Low power consumption and large capacity Lithium battery (1500mAh), 4~5 days standby
7. Powered by rechargeable battery, power adapter, or car charger (specified models)
8. Higher print speed 90mm/sec
9. 50km thermal printer head life
10. Multiple languages supported
11. ESC/POS command set compatible

## Specification

Model	OCPM-M06
Name	58mm mini portable bluetooth thermal printer
Color	Black
Interface	USB, RS-232, Bluetooth (optional)
Battery	7.4V DC/ 1500mAh rechargeable li-ion battery
Power adaptor	DC 9v/1.5-2A
Standby time	4-5days after fully charged
Buffer	Input buffer:Up to 20K,Flash:256K
Other function	Paper detection, Power detection, Manual shut down, 1D&QR Code Print
Device name	Can be customized
TPH life	50KM
Password	Enter default pairing code "1234", it can be customized or change by customers, At max 6 digitals
Accessories	Data cable, power adaptor, power cord, paper roller, CD, manual
Power plug dimension	3.5*1.1mm
OS supporting	Windows & Android & IOS Systems
Safety standards	CE ,FCC,Rohs etc
Printing method	Direct thermal line
Resolution	203DPI (8dot/mm)
Printing speed	70mm/sec (Max 90mm/sec)
Print width	48mm
Continuous printing	120 pieces Thermal Roll for fully charged battery
Characters per Line	Font A:32 character /Line Simple, traditional Chinese:16 character /Line
Printing Command	Compatible with ESC/POS
Character size	FontA: 12*24dots, 1.5(W)*3.0(H) Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm

Character set	Alphanumeric/ Chinese Kanji
<b>Media</b>	
Paper type	Thermal roll paper
Paper width	57.5±0.5mm
Paper feeding method	Easy paper loading
Paper roll diameter	40mm Max
Paper thickness	0.06-0.08mm
<b>Physical</b>	
Dimension	105*75*45mm
Weight	Net:360g Gross:440g
Package box	190*120*70 mm
40 in 1 carton	380*475*340mm/18.36kg
<b>Environment</b>	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation





**ocom**  
At your side

MODE POWER FEED



OCPP-M06

58MM Portable Thermal Printer



ocom  
All your data.

MODE

POWER

FEED

OCPP-M06  
58MM Portable Thermal Printer

COM

USB



>>>Self test<<<  
58-II Thermal Printer



Version : MN-C-Z02-AA  
Revised date: 24-Jul-2015  
Command standard: EPSON(ESC/POS)  
Print mode: Normal mode  
Hex mode  
Print method: Line thermal  
Print width:

>>>Self test<<<  
58-II Thermal Printer



Version : MN-C-Z02-AA  
Revised date: 24-Jul-2015  
Command standard: EPSON(ESC/POS)  
Print mode: Normal mode  
Hex mode  
Print method: Line thermal  
Print width:



OCPP-M06  
58MM Portable Thermal Printer

MODE POWER FEED

>>>Comp test<<<

Bluetooth Name:\*\*\*N0\*\*  
012345678901



华网资讯网  
西安捷通得泰条码设备有限公司  
西安捷通得泰条码设备有限公司  
地址: 西安市高新区唐都路111号  
邮编: 710065  
电话: 029-88521111  
网址: www.jtbarcode.com



58-II Thermal Printer

>>>Self test<<<



