

58mm Mini Portable Bluetooth Thermal Printer

(M/N:OCPM-M06)

Features:

1. Mini size suitable for portable application
2. Windows, Java, Linux, Android (or Android +IOS) operation system supported
3. Bluetooth, USB and RS232 communication supported
4. SDK for Android available
5. One printer can connect up to 8 smart devices (7 Android, one Apple device) via bluetooth
6. Low power consumption and large capacity Lithium battery (1500mAh), 4~5 days standby
7. Powered by rechargeable battery, power adapter, or car charger (specified models)
8. Higher print speed 90mm/sec
9. 50km thermal printer head life
10. Multiple languages supported
11. ESC/POS command set compatible

Specification

Model	OCPM-M06
Name	58mm mini portable bluetooth thermal printer
Color	Black
Interface	USB, RS-232, Bluetooth (optional)
Battery	7.4V DC/ 1500mAh rechargeable li-ion battery
Power adaptor	DC 9v/1.5-2A
Standby time	4-5days after fully charged
Buffer	Input buffer:Up to 20K,Flash:256K
Other function	Paper detection, Power detection, Manual shut down, 1D&QR Code Print
Device name	Can be customized
TPH life	50KM
Password	Enter default pairing code "1234", it can be customized or change by customers, At max 6 digitals
Accessories	Data cable, power adaptor, power cord, paper roller, CD, manual
Power plug dimension	3.5*1.1mm
OS supporting	Windows & Android & IOS Systems
Safety standards	CE ,FCC,Rohs etc
Printing method	Direct thermal line
Resolution	203DPI (8dot/mm)
Printing speed	70mm/sec (Max 90mm/sec)
Print width	48mm
Continuous printing	120 pieces Thermal Roll for fully charged battery
Characters per Line	Font A:32 character /Line Simple, traditional Chinese:16 character /Line
Printing Command	Compatible with ESC/POS
Character size	FontA: 12*24dots, 1.5(W)*3.0(H) Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm

Character set	Alphanumeric/ Chinese Kanji
Media	
Paper type	Thermal roll paper
Paper width	57.5±0.5mm
Paper feeding method	Easy paper loading
Paper roll diameter	40mm Max
Paper thickness	0.06-0.08mm
Physical	
Dimension	105*75*45mm
Weight	Net:360g Gross:440g
Package box	190*120*70 mm
40 in 1 carton	380*475*340mm/18.36kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation





ocom
At your side

MODE POWER FEED



OCPP-M06

58MM Portable Thermal Printer



ocom
All your data

MODE

POWER

FEED

OCPP-M06
58MM Portable Thermal Printer

COM

USB



>>>Self test<<<

58-II Thermal Printer



Version : MN-C-Z02-AA
Revised date: 24-Jul-2015
Command standard:EPSON(ESC/POS)
Print mode: Normal mode
Hex mode
Line thermal
Print method: Line thermal
Print width:

>>>Self test<<<

58-II Thermal Printer



Version : MN-C-Z02-AA
Revised date: 24-Jul-2015
Command standard:EPSON(ESC/POS)



MODE POWER FEED
OCPP-M06
58MM Portable Thermal Printer

バージョン
改訂日
コマンド標準
印刷モード
Hexモード
線熱転写
印刷方法
印刷幅

Version : MN-C-Z02-AA
Revised date: 24-Jul-2015
Command standard:EPSON(ESC/POS)
Print mode: Normal mode
Hex mode
Line thermal
Print method: Line thermal
Print width:



58-II Thermal Printer

>>>Self test<<<

>>>Comp Test<<<

Bluetooth Name:***N0**

012345678901



中国国内総生産額は、2015年7月24日に改訂されました。また、印刷モードとして「Hexモード」を追加しました。また、印刷方法を「線熱転写」に変更しました。印刷幅は変更ありません。



