

(OCPP-M15)Mini Portable Thermal Printer Bluetooth Impresora Mobile Receipt Barcode Printer

(M/N:OCPP-M15)

Features:

Windows,Android ,IOS operation system supported
SDK for Android /IOS available
1D, 2D barcode (QR code/ PDF417) Supported
image printing supported
Can change the printer name, password, baud rate online
2000mAh 18650 battery package
Support USB port charge
Higher print speed 70mm/sec
50Km thermal printer head life
Multiple languages supported
ESC/POS command set compatible

Specifications:

General	
Model	OCPP-M15
Name	58mm mini portable bluetooth thermal printer
Color	Black
Interface	USB/Bluetooth4.0
Battery	7.4V DC/ 2000mAh rechargeable li-ion battery
Power adaptor	DC 5v/2A
Standby time	4days after fully charged
Buffer	Input buffer:Up to 50K,Flash:256K
TPH Life	50KM
Password	Enter default pairing code "1234", it can be customized or change by customers, At max 6 digitals
Other function	Paper detection, Power detection, Manual shut down, 1D&QR Code Print; Led indicator; Big Paper Warehouse; Quick-acting USB Charging
Accessories	Data cable,power adaptor,paper roller,CD,manual
Power plug dimension	3.5*1.1mm
OS supporting	Windows &Android & IOS Systems
Safety standards	CE ,FCC,Rohs etc
Printing capability	
Printing method	Direct thermal line
Resoluiton	203DPI (8dot/mm)
Printing speed	70mm/sec (Max 90mm/sec)
Print width	48mm
Continuous printing	120 pieces Thermal Roll for fully charged battery
Characters per Line	Font A:32 character /Line Simple,traditional Chinese:16 character /Line
Printing Command	Compatible with ESC/POS
Barcode and character	

Character size	FontA: 12*24dots, 1.5(W)*3.0(H) Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Character set	Alphanumeric/ Chinese Kanji
Media	
Paper type	Thermal roll paper
Paper width	57.5±0.5mm
Paper feeding method	Easy paper loading
Paper roll diameter	40mm Max
Paper thickness	0.06-0.08mm
Physical	
Dimension	112*83*54mm
Weight	Net:230g Gross:450g
Package box	180*122*65 mm
40 in 1 carton	372*372*500mm/19.4kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation

Product Overview:













