China factory made high quality portable pos terminal with printer (M/N: P8000)

Android 4.4 operation system.

Adopts Qualcomm quad-core 1.2GHz processor.

4.0 inches IPS capacitive touch screen.

Safety and reliable design

Passed Unionpay Pboc L1& L2: passed PIN input safety certification.

Unionpay direct connect POS network access.

Support Printing Receipt and Barcode reading

Supports magnetic stripe card, IC card, contactless card.

System Parameters	
CPU	Qualcomm quad-core 1.2GHz
os	Android 4.4
RAM/ROM	ROM 512MB eMMC; RAM 512MB DDR2;
	support external micro SD card, 32 GB at most
Display	4.0 inch capacitive, multi touch; 480*800, IPS display
Keypad	3 Touch System Keys, 15 physical keys (include Power key, Custom key, POS Cipher key and Command key)
Battery	Lithium polymer battery, 5700mAh
Functional Configuration	•
Camera	Rear Camera 5M AF (support flashlight), Front Camera 0.3M wide angle
Printer	Bullt-in 2 inches thermal printer
Navigation	Built-in GPS, support AGPS
Indicator Light	System indicator light, POS indicator light
Audios	Built-in speaker, buzzer, microphone, vibrator
Sensors	Gravity sensor
POS	provey serior
Sound Wave Payment	Support
Magnetic Strip Card	Triple track MSR, bi-directional swiping ISO7811, 7812
IC Card	1 Solt, Support 1.8W3V/SV, ISO7816, PBOC and EMV
Contactless card	13.56MHz, ISO/IEC 14443 Type A/B, g/BOC
SAM Card	15.30m/nz, 130/16C 14443 Type A/B, 4FBCC
Cipher Keyboard	Built-in keypad
Network Parameters	L
Network Type	WCDMA/GSM
Network Spectrum	WCDMA 2100MHz
	GSM/GPRS/EDGE 850/900/1800/1900MHz
WLAN	802.11 a/b/g/n Built-in Antenna
Voice/Data Service	Support
WPAN	Bluetooth V4.0 ÷ EDR
External Interface	
USB Interface	Micro USB2.0, support USB OTG
Charger Jack	DC JACK
Power Supply Jack	Pogo Pin, 5V500mA
Communication	USB, RS232
Physical Parameters	
Dimensions	205mm H * 82mm/67mm W * 33mm D
Weight	500g (battery included)
Operating Temp	-20°C ~ 60°C
Storage Temp	-40°C ~ 80°C
Humidity	10%~90% RH non-condensing
Drop Test	1.0-meter drop protection
Roller Drop Test	500 times
ESD protection	±8KV contact discharge; ±15KV air discharge
Development Environment	, 200 - 100 -
System Environment	Android 4.4/SP-UI
Development Environment	SDK
Management Software	PC management suite/MDM
- maganian and an	[