

# POS-1513 15.1 inch restaurant ordering and billing pos machine all in one touch screen pos system

(M/N:POS-1513)

OCOM 1513 series POS terminal has aluminium alloy shell and base,It has intel Celeron and intel core I serie CPU for option,it is easy to install second display,MSR, VFD as modules.This model is very convenient for maintenance by removing the back cover and it has rich I/O interfaces to be connected to more external devicesThis model is very convenient for maintenance and it has rich I/O interfaces to be connected to more external devices

## Features:

Intel Celeron series and intel core I3 I5 processor for option

Rockchip high speed RK3288 processor for option

EMMC 8GB/16GB/32GB for option

Hard Driver Msata SSD 64GB ,SSD 128GB and 256 GB for option

Multi-point projected capacitive touch panel

Optional side MSR and VFD220 customer display mounted to back cover

Ture flat and water-proof scratch-resistant surface display

## Specification

Model	POS-1513W	POS-1513A
Name	15.1 inch aluminium alloy touch POS terminal	
Housing	aluminium alloy shell machine body and base	
Color	whole black color machine	
Main screen	15.1 inch touch screen monitor	
Resoluiton	1024*768	
Brightness	250cd/m <sup>2</sup>	
View angle	Horizon: 160; Vertical :150	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	9.7 inch display W/o touch function	
Customer display	2*20 VFD or 2*20 LCD display mounted to back cover for option	
<b>Performance</b>		
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4 <sup>th</sup> generation CPU for option	Rockchip series RK3288 ,quad core 1.8G, RK3399 for option
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB usually ,2GB/8GB for option	On board DDRIII 1GB,2GB,4GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB	on board8GB,16GB ,32GB EMMC for option

Audio	On board Real Tek ALC662	on board Real Tek ALC5640 audio chip
LAN	10/100Mbps,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10/100Mbps,Realtek RTL8111F Lan chip□Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support
Operating System	Windows7/8/10, Embedded,WEPOS,Linux	Up to Android 8.1
<b>Connectivity</b>		
External I/O port(J1900/RK3288)	power button*1	
	12V DC in jack*1	
	LAN:RJ-45*1	
	USB*4	
External I/O port J1900	15PIN D-sub VGA *1	
	HDMI*1 or RS 232*1 for option	
	line out*1,MIC in*1	
External I/O port RK3288	Audio out*1	
	TF card port*1	
	RJ11 for cash drawer*1	
	RS 232*1	
<b>Options</b>		
MSR	optional side MSR	
<b>Environment</b>		
Operating temperature	0 to 40 degrees centigrade	
Storage temperature	-10 to 60 degrees centigrade	
Working humidity	10%~80% No condensation	
Storage humidity	10%~90% No condensation	
<b>Package</b>		
Weight	Net 5.5Kg, Gross 7.0Kg	
Package with foam inside	440*290*425mm	
<b>Accessories</b>		
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available	
<b>Other</b>		
Compliance	FCC Class A/CE Mark/LVD/CCC	















