

## **15-inch Touch POS terminal With Aluminum Base**

(M/N: POS-1513P)

OCOM 1513P POS terminal has aluminium alloy base, It has intel Celeron and intel core I series CPU for option, it is easy to install 2<sup>nd</sup> display, MSR, VFD as modules. This model is very convenient for maintenance by removing the back cover and it has rich I/O interfaces to be connected more external devices.

### Features:



Intel Celeron series and intel core I3 I5 processor for option;

Hard Driver Msata SSD 64GB, SSD 128GB and 256 GB for option;

Multi-point projected capacitive touch panel;

3-track MSR and VFD220 customer display for option;

Ture flat and water-proof scratch-resistant surface display.

## Applications:

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop;

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop;

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket;

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf.

## Parameter

Model	POS-1513P
Name	15.1 inch aluminium alloy touch POS terminal
Housing	Plastic shell body and aluminium alloy base
Color	whole black color machine
Display	
Main screen	15.1 inch touch screen monitor
Resolution	1024*768
Brightness	250cd/m2
View angle	Horizon: 160; Vertical :150
Touch screen	Multi-point projected G+G capacitive touch
Sub-display	9.7 inch display W/o touch function
Customer display	2*20 VFD display mounted to back cover for option
Performance	
Motherboard	Intel Celeron J4125, 2.0GHz or intel core I3 / I5 4th CPU for option
System Memory	1*SO-DIMM DDR4 slot, support2400mHZ ,4GB/8GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB
Audio	On board Real Tek ALC662
LAN	10/100Mbs, Realtek RTL8111F Lan chip built in Mini PCI-E slot, support embedded WIFI module
Operating System	Supporting Windows 10/11
Connectivity	

External I/O port(J4125)	Power button*1
	12V DC in jack*1
	LAN: RJ-45*1
	USB*6
	15PIN D-sub VGA *1
	RS232*2
	Line out*1, Mic in*1
Options	
MSR	3-track MSR
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Package	
Weight	Net 5.5Kg, Gross 7.0Kg
Package with foam inside	440*290*425mm
Accessories	
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
Other	
Compliance	FCC Class A/CE Mark/LVD/CCC















