

# 15.6/15.1/12.1 Inch All in one touch screen POS Terminal With built-in Thermal Printer

(M/N:POS-C15/C12)

## Features:

- 1 Intel Celeron Processor J1900 Quad core 2.0GHz HighConfiguration CPU for Windows system
- 1 1.8GHz Quad-core RK3288 Chip Cortex-A17 Processor for Android system
- 1 2GB RAM+8GB ROM standard (Android)
- 1 2GB RAM+32GB SSD standard (Windows)
- 1 11.6/15.6 inches main capacitive touch screen
- 1 Built-in 58/80mm big gear thermal printer for options
- 1 Magnetic member card reader for optional
- 1 VFD customer display or vice screen

## Applications:

- 1 Catering: hotel,restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- 1 Retailer: Business Street,boutique, department store, cosmetics shop and high-class barbershop
- 1 Recreation: sauna, spa,night club, theme park, casino and point of sales for lottery ticket
- 1 Commercial: informationmanagement terminals for parking lot, inn, aviation, subway, station and wharf

## Pictureshow:



## Parameter

Model	POS-C15/C12
Color	Silver-gray , White or Black
CPU①	Intel Celeron J1900 Quad core 2.0 GHZ
CPU②	1.8GHz Quad-core RK3288 Chip Cortex-A17 Processor
Memory①	DDRIII 1066/1333*1 2GB (default) (Windows)
Memory②	2GB RAM 8GB ROM ①Android②
OS①	Windows7(Beta)
OS②	Android 5.1
Hard Driver	SSD 32GB (default) (Windows)
LCD panel Size	15.6/15.1/12.1 inch TFT LCD
Brightness	350cd/m2
Resolution	1366*768(max)
Touch Screen	Capacitive touch screen
Printer Parameter	Print Density 203dpi
	Printing Command ESC/POS
	Paper Roll Diameter 60mm
	Paper Width 58mm or 80mm
	Printing Speed 60mm/s or 150mm/s
	MCBF(life) 50km

Other optinoal funtion	MSR/ VFD220 customer displaiy/ vice screen
View Angle	Horizon: 150; Vertical :140
	1* power button 12V DC in jack*1
	HDMI*1
	VGA(15Pin D-sub)*1
I/O port□J1900□	LAN:RJ-45*1
	USB(2.0)*4
	RS232*2
	MIC IN*1 Audio out*1
	RJ11*1 (Optional)
	TF slot *1
I/O port□A83T□	RJ45*1
	HDMI for vice screen
	DB9 RS232 port*1□USB*2
	Audio*1
Operating temperature	0°C to 40°C
Storage temperature	-20°Cto 60°C
Operating System	Windows XP above, Embedded,WEPOS,Linux
Power adapter	110-240V/50-60HZ AC power, Input DC12/5A out put