

| | |
|--------------------------|--|
| Model | POS-1519 |
| Name | 15.1 inch all in one touch POS terminal |
| Housing | Plastic shell machine body and aluminium base |
| Color | whole black color machine |
| | |
| Main screen | 15.1 inch touch screen monitor |
| Resolution | 1024*768 |
| Brightness | 2 250cd/m |
| View angle | Horizon: 150; Vertical :140 |
| Touch screen | Multi-point projected G+G capacitive touch |
| Sub-display | 15.1 inch display or 12.1inch display W/o touch function for option |
| Customer display | 2*20 VFD or 2*20 LCD display mounted to back cover for option |
| Performance | |
| Motherboard | Intel Celeron Bay Trail J1900 2.0GHz, or Intel Celeron J4125,intel core I3 / I5 CPU for option |
| System Memory | 1*SO-DIMM DDRIII slot, 4GB DDR3L/1333, 8GB for option |
| Storage device | M SATA SSD 64GB or higher, up to 256GB |
| Audio | On board Real Tek ALC662 |
| LAN | 10/100Mbps, Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module |
| Operating System | Windows7/8/10, Embedded,WEPOS,Linux |
| Connectivity | |
| External I/O port J1900 | power button*1,12V DC in Jack*1 |
| | LAN:RJ-45*1 |
| | USB*6 |
| | 15PIN D-sub VGA *1 |
| | RS 232*2 |
| | line out*1,MIC in*1 |
| Options | |
| MSR | optional side MSR |
| Package | |
| Weight | Net 6.5Kg, Gross 8.0Kg for single screen |
| Package with foam inside | 425*275*405mm for single screen, 440*295*425mm for dual screen |
| Environment | |
| Operating temperature | 0 to 40 degrees centigrade |
| Storage temperature | -10 to 60 degrees centigrade |
| Working humidity | 10%~80% No condensation |
| Storage humidity | 10%~90% No condensation |
| Accessories | |
| Power adapter | 200-240V/50-60HZ(default) , 110-240V/50-60HZ AC power input ,DC12V/5A output adaptor |
| Power cable | Power cable plug compatible with USA /EU / UK etc and customized available |

Application



Bar



Restaurant



Coffee Store



Mile Tea Store



Bakery



Convenience Store



Library



Supermarket