

|                                 |  |   |
|---------------------------------|--|---|
| Model                           | POS-1513W  | POS-1513A   |
| Name                            | 15.1 inch aluminium alloy touch POS terminal   |   |
| Housing                         | aluminium alloy shell machine body and base  |   |
| Color                           | whole black color machine  |   |
|                                 |  |   |
| Main screen                     | 15.1 inch touch screen monitor   |   |
| Resoluiton                      | 1024*768   |   |
| Brightness                      | 250cd/m <sup>2</sup>   |   |
| View angle                      | Horizon: 160; Vertical :150  |   |
| Touch screen                    | Multi-point projected G+G capacitive touch   |   |
| Sub-display                     | 9.7 inch display W/o touch function  |   |
| Customer display                | 2*20 VFD or 2*20 LCD display mounted to back cover for option  |   |
| <b>Performance</b>              |  |   |
| Motherboard                     | Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4 <sup>th</sup> generation CPU for option | Rockchip series RK3288 ,quad core 1.8G, RK3399 for option                         |
| System Memory                   | 1*SO-DIMM DDRIII slot, support1333*/1600 4GB usually ,2GB/8GB for option                                     | On board DDRIII 1GB,2GB,4GB for option  |
| Storage device                  | Msata SSD 64GB or higer, up to 256GB   | on board8GB,16GB ,32GB EMMC for option  |
| Audio                           | On board Real Tek ALC662   | on board Real Tek ALC5640 audio chip  |
| LAN                             | 10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module                    | 10/100Mbs,Realtek RTL8111F Lan chip□Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support |
| Operating System                | Windows7/8/10, Embedded,WEPOS,Linux  | Up to Android 8.1   |
| <b>Connectivity</b>             |  |   |
| External I/O port(J1900/RK3288) | power button*1   |   |
|                                 | 12V DC in jack*1   |   |
|                                 | LAN:RJ-45*1  |   |
|                                 | USB*4  |   |
| External I/O port J1900         | 15PIN D-sub VGA *1   |   |
|                                 | HDMI*1 or RS 232*1 for option  |   |
|                                 | line out*1,MIC in*1  |   |
| External I/O port RK3288        | Audio out*1  |   |
|                                 | TF card port*1   |   |
|                                 | RJ11 for cash drawer*1   |   |
|                                 | RS 232*1   |   |
| <b>Options</b>                  |  |   |
| MSR                             | optional side MSR  |   |
| <b>Environment</b>              |  |   |
| Operating temperature           | 0 to 40 degrees centigrade   |   |
| Storage temperature             | -10 to 60 degrees centigrade   |   |
| Working humidity                | 10%~80% No condensation  |   |
| Storage humidity                | 10%~90% No condensation  |   |
| <b>Package</b>                  |  |   |
| Weight                          | Net 5.5Kg, Gross 7.0Kg   |   |
| Package with foam inside        | 440*290*425mm  |   |
| <b>Accessories</b>              |  |   |
| Power adapter                   | 110-240V/50-60HZ AC power input ,DC12V/5A output adaptor   |   |

|             |  |
|-------------|--|
| Power cable | Power cable plug compatible with USA /EU / UK etc and customized available |
| Other       |  |
| Compliance  | FCC Class A/CE Mark/LVD/CCC  |