20X2Characters Double Line VFD Customer Display

(Model No.:VFD220C)

Features:

1 Doublelines 20*2 characters VFD display;

1 Support 26 countries languages;

l Poleheight is adjustable;

1360degree rotation angle;

l SupportsESC/POS and CD5220 command l 3kinds of different height for you choose

Specifications:

l Highbrightness Vacuum Fluorescent Display for excellent visibility over a wideviewing angle.

l Availablein 9mm high characters.

140characters in 20 columns by 2 lines format.

l Thirteensets of international characters, plus one set of user defined charactersallows total flexibility in display fonts.

l Easyprogramming using Escape sequence commands.

l Emulation of Aedex, Epson and DSP800 command sets.

l Displaycan swivel and tilt to a wide range of angles.

l Adjustabledisplay height.

l Powermay be sourced from system, with the bracket and cable kit supplied in typicalconfiguration.

l ACadaptors in various configurations for all AC voltages.

Frame color Black / white/Cyan

Display Color Blue-Green

Display Method Vacuum Fluorescent Display

Display Mode 2lines*20characters

Brightness 700cd/m2

Character type 96 alphanumeric, 26Kinds of international character set

Character font5X7 Dot matrixCharacter size6.75mm x 3.75mmDot Size0.8 x 0.55 mm

Viewing Area -5~60°

Panel Dimension 204(W)*67(H)*40(D)

Viewing Angle 188mm(L)×40mm∏W∏

Horizontal Rotation

Language

Code page

Max 350°

Weight 0.9KG

Commands Mode ESC/POS/CD5220/DSP800/UTC.....

20 Code page

US English, UK English, Turkish, Bosnia, Croatian, Czech, Danish, Dutch, Estonian,

Faroese, Finnish, Flemish, French, Fr Canadian, German, Greek, Hebrew, Hungarian, Icelandic, Indonesian, Irish, Italian, Katakana, Latvian, Lithuanian,

Norwegian, Polish, Portuguese, Romanian, Russian, Slovene, Slovak, Spanish,

Swedish...

Interface RS232 (serial) or USB

Baudrate 2400/9600 BPS,

MTBF 40,000 hours

Power supply DC5V 1A

Certificate CE,ROHS,FCC

